



### **TE120B220RJ Information**

Heisener.com

Part Number TE120B220RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 220 OHM 5% 120W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **TE120B220RJ Specifications**

Manufacturer Part NumberTE120B220RJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance220 OhmsTolerance±5%Power (Watts)120WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 7.165" L (28.00mm x 182.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Report errors?		
CategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance220 OhmsTolerance±5%Power (Watts)120WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 7.165" L (28.00mm x 182.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	TE120B220RJ
Chassis Mount Resistors  Package Radial, Tubular  TE, CGS  Resistance 220 Ohms  Tolerance ±5%  Power (Watts) 120W  Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm)  Height - Seated (Max) - Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageRadial, TubularSeriesTE, CGSResistance220 OhmsTolerance±5%Power (Watts)120WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 7.165" L (28.00mm x 182.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesTE, CGSResistance220 OhmsTolerance±5%Power (Watts)120WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 7.165" L (28.00mm x 182.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance220 OhmsTolerance±5%Power (Watts)120WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 7.165" L (28.00mm x 182.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±5%  Power (Watts) 120W  Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Series	TE, CGS
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±440ppm/°C  Operating Temperature  -25°C ~ 225°C  Features  Flame Proof, Safety  Coating, Housing Type  Silicone Coated  Mounting Feature  Brackets  Size / Dimension  1.102" Dia x 7.165" L (28.00mm x 182.00mm)  Height - Seated (Max)  -  Lead Style  Package / Case  Radial, Tubular  Failure Rate  -	Resistance	220 Ohms
Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Power (Watts)	120W
Operating Temperature  -25°C ~ 225°C  Features  Flame Proof, Safety  Coating, Housing Type  Silicone Coated  Mounting Feature  Brackets  Size / Dimension  1.102" Dia x 7.165" L (28.00mm x 182.00mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -  -25°C ~ 225°C  Elame Proof, Safety  Silicone Coated  Silicone Coated  Brackets  1.102" Dia x 7.165" L (28.00mm x 182.00mm)  -  Lead Style  Solder Lugs  Radial, Tubular	Composition	Wirewound
Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type  Silicone Coated  Mounting Feature  Brackets  Size / Dimension  1.102" Dia x 7.165" L (28.00mm x 182.00mm)  Height - Seated (Max)  - Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  Silicone Coated  Brackets  1.102" Dia x 7.165" L (28.00mm x 182.00mm)  - Rate	Operating Temperature	-25°C ~ 225°C
Mounting Feature Brackets Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Features	Flame Proof, Safety
Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Coating, Housing Type	Silicone Coated
Height - Seated (Max)  Lead Style  Package / Case  Radial, Tubular  Failure Rate  -	Mounting Feature	Brackets
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	1.102" Dia x 7.165" L (28.00mm x 182.00mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

#### **TE120B220RJ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **TE120B220RJ Payment Methods**

































If you have any question about TE120B220RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com