



TE120B56RJ Information

Heisener.com

Part Number TE120B56RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 56 OHM 5% 120W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TE120B56RJ Specifications

Manufacturer Part NumberTE120B56RJManufacturerTE Connectivity Passive ProductCategoryResistorsChassis Mount ResistorsPackageRadial, TubularSeriesTE, CGSResistance56 OhmsTolerance±5%Power (Watts)120WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, Safety
Category Resistors Chassis Mount Resistors Package Radial, Tubular TE, CGS Resistance 56 Ohms Tolerance ±5% Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature
Chassis Mount Resistors Package Radial, Tubular Series TE, CGS Resistance 56 Ohms Tolerance ±5% Power (Watts) 120W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C
PackageRadial, TubularSeriesTE, CGSResistance56 OhmsTolerance±5%Power (Watts)120WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°C
SeriesTE, CGSResistance 56 Ohms Tolerance $\pm 5\%$ Power (Watts) $120W$ CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Resistance 56 Ohms Tolerance $\pm 5\%$ Power (Watts) $120W$ CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Tolerance $\pm 5\%$ Power (Watts) 120W Composition Wirewound Temperature Coefficient $\pm 440 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Power (Watts) 120W Composition Wirewound Temperature Coefficient $\pm 440 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Temperature Coefficient $\pm 440 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Features Flame Proof, Safety
2 1001, 80100,
Coating, Housing Type Silicone Coated
Mounting Feature Brackets
Size / Dimension 1.102" Dia x 7.165" L (28.00mm x 182.00mm)
Height - Seated (Max)
Lead Style Solder Lugs
Package / Case Radial, Tubular
Failure Rate -
Report errors?

TE120B56RJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TE120B56RJ Payment Methods



















TE120B56RJ Shipping Methods













If you have any question about TE120B56RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com