



## **TE2500B15RJ Information**



For Reference Only

Part Number TE2500B15RJ

Manufacturer TE Connectivity Passive Product

**Category** Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 15 OHM 5% 2500W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **TE2500B15RJ Specifications**

Manufacturer Part NumberTE2500B15RJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance15 OhmsTolerance±5%Power (Watts)2500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension2.362" Dia x 23.622" L (60.00mm x 600.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Report errors?		
CategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance15 OhmsTolerance±5%Power (Watts)2500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension2.362" Dia x 23.622" L (60.00mm x 600.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	TE2500B15RJ
Chassis Mount Resistors  Package Radial, Tubular  TE, CGS  Resistance 15 Ohms  Tolerance ±5% Power (Watts) 2500W Composition Wirewound  Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 2.362" Dia x 23.622" L (60.00mm x 600.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageRadial, TubularSeriesTE, CGSResistance15 OhmsTolerance±5%Power (Watts)2500WCompositionWirewoundTemperature Coefficient±440pm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension2.362" Dia x 23.622" L (60.00mm x 600.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesTE, CGSResistance15 OhmsTolerance±5%Power (Watts)2500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension2.362" Dia x 23.622" L (60.00mm x 600.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance 15 Ohms  Tolerance ±5%  Power (Watts) 2500W  Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 2.362" Dia x 23.622" L (60.00mm x 600.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Package	Radial, Tubular
Tolerance ±5%  Power (Watts) 2500W  Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 2.362" Dia x 23.622" L (60.00mm x 600.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Series	TE, CGS
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±440ppm/°C  Operating Temperature  -25°C ~ 225°C  Features  Flame Proof, Safety  Coating, Housing Type  Silicone Coated  Mounting Feature  Brackets  Size / Dimension  2.362" Dia x 23.622" L (60.00mm x 600.00mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -	Resistance	15 Ohms
Composition  Temperature Coefficient  ±440ppm/°C  Operating Temperature  -25°C ~ 225°C  Features  Flame Proof, Safety  Coating, Housing Type  Silicone Coated  Mounting Feature  Brackets  Size / Dimension  2.362" Dia x 23.622" L (60.00mm x 600.00mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 2.362" Dia x 23.622" L (60.00mm x 600.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Power (Watts)	2500W
Operating Temperature  -25°C ~ 225°C  Features  Flame Proof, Safety  Coating, Housing Type  Silicone Coated  Mounting Feature  Brackets  Size / Dimension  2.362" Dia x 23.622" L (60.00mm x 600.00mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -	Composition	Wirewound
Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 2.362" Dia x 23.622" L (60.00mm x 600.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type  Silicone Coated  Mounting Feature  Brackets  Size / Dimension  2.362" Dia x 23.622" L (60.00mm x 600.00mm)  Height - Seated (Max)  - Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -	Operating Temperature	-25°C ~ 225°C
Mounting Feature  Size / Dimension  2.362" Dia x 23.622" L (60.00mm x 600.00mm)  Height - Seated (Max)  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -	Features	Flame Proof, Safety
Size / Dimension 2.362" Dia x 23.622" L (60.00mm x 600.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Coating, Housing Type	Silicone Coated
Height - Seated (Max)  Lead Style  Package / Case  Radial, Tubular  Failure Rate  -	Mounting Feature	Brackets
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	2.362" Dia x 23.622" L (60.00mm x 600.00mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

#### **TE2500B15RJ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **TE2500B15RJ Payment Methods**





















## **TE2500B15RJ Shipping Methods**













If you have any question about TE2500B15RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com