



TE300B33RJ Information

Heisener.com

Part Number TE300B33RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 33 OHM 5% 300W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TE300B33RJ Specifications

Manufacturer Part NumberTE300B33RJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance33 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.575" Dia x 11.102" L (40.00mm x 282.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Report errors?		
CategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance33 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.575" Dia x 11.102" L (40.00mm x 282.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	TE300B33RJ
Chassis Mount Resistors Package Radial, Tubular TE, CGS Resistance TE, CGS Resistance 33 Ohms Tolerance ±5% Power (Watts) Some (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageRadial, TubularSeriesTE, CGSResistance33 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440pm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.575" Dia x 11.102" L (40.00mm x 282.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesTE, CGSResistance33 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.575" Dia x 11.102" L (40.00mm x 282.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance 33 Ohms Tolerance ±5% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Series	TE, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Resistance	33 Ohms
Composition Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate Wirewound #440ppm/°C -25°C ~ 225°C Flame Proof, Safety Silicone Coated #440ppm/°C -25°C ~ 225°C Flame Proof, Safety Silicone Coated #440ppm/°C -25°C ~ 225°C Flame Proof, Safety Silicone Coated #440ppm/°C #440	Tolerance	±5%
Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Power (Watts)	300W
Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Composition	Wirewound
Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Operating Temperature	-25°C ~ 225°C
Mounting Feature Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate Brackets Solder Lugs Radial, Tubular	Features	Flame Proof, Safety
Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Silicone Coated
Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	1.575" Dia x 11.102" L (40.00mm x 282.00mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

TE300B33RJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TE300B33RJ Payment Methods



















TE300B33RJ Shipping Methods













If you have any question about TE300B33RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com