



TE300B600RJ Information

Heisener.com

Part Number TE300B600RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 600 OHM 5% 300W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TE300B600RJ Specifications

Manufacturer Part NumberTE300B600RJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageChassis Mount ResistorsPackageRadial, TubularSeriesTE, CGSResistance600 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.575" Dia x 11.102" L (40.00mm x 282.00mm)Height - Seated (Max)-		
CategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance600 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Manufacturer Part Number	TE300B600RJ
Chassis Mount Resistors Package Radial, Tubular Series TE, CGS Resistance 600 Ohms Tolerance ±5% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension Chassis Mount Resistors Radial, Tubular **Examples** 600 Ohms ±45% 600 Ohms ±5% 600 Ohms 500 Ohms 600	Manufacturer	TE Connectivity Passive Product
PackageRadial, TubularSeriesTE, CGSResistance600 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Category	Resistors
SeriesTE, CGSResistance600 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.575" Dia x 11.102" L (40.00mm x 282.00mm)		Chassis Mount Resistors
Resistance 600 Ohms Tolerance ±5% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Series	TE, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 300W Wirewound ±440ppm/°C -25°C ~ 225°C Safety Silicone Coated Mounting Type Silicone Coated 1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Resistance	600 Ohms
Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Tolerance	±5%
Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Power (Watts)	300W
Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Composition	Wirewound
Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Temperature Coefficient	±440ppm/°C
Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Operating Temperature	-25°C ~ 225°C
Mounting Feature Brackets Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Features	Flame Proof, Safety
Size / Dimension 1.575" Dia x 11.102" L (40.00mm x 282.00mm)	Coating, Housing Type	Silicone Coated
·	Mounting Feature	Brackets
Height - Seated (Max) -	Size / Dimension	1.575" Dia x 11.102" L (40.00mm x 282.00mm)
	Height - Seated (Max)	-
Lead Style Solder Lugs	Lead Style	Solder Lugs
Package / Case Radial, Tubular	Package / Case	Radial, Tubular
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

TE300B600RJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TE300B600RJ Payment Methods



















TE300B600RJ Shipping Methods













If you have any question about TE300B600RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com