

TE30A1203B01

TE30A1203B01 Information

		Part Number	TE30A1203B01	
		Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	8588
	e an ar	Category	Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters	19 1 1
	- 91	Description	AC/DC WALL MOUNT ADAPTER 12V 30W	
		Package	-	
			For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



TE30A1203B01 Specifications

Manufacturer Part NumberTE30A1203B01ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesTE30Region UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)30WNo Load Power ConsumptionIDen Wink MaxiPolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature20°C ~ 40°COutput ConnectorBarrel Plug. 2.5.7m ND. x.9.5mm OD. x.9.5mm		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series TE30 Region Utilized North America Form Wall Mount Input Type Fixed Blade, Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications TE (Commercial) Efficiency Level VI Output Connector Barrel Plug. 2.5mm I.D. x 5.5mm O.D. x 9.5mm x 33.6mm)	Manufacturer Part Number	TE30A1203B01
AC DC Desktop, Wall Adapters Package - Series TE30 Region Utilized North America Form Wall Mount Input Type Fixed Blade, Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature -20°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesTE30Region UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2.5APower (Watts)00mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm, 33.6mm)	Category	Power Supplies - External/Internal (Off-Board)
Series TE30 Region Utilized North America Form Wall Mount Input Type Fixed Blade, Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Voltage - Output 2.5A Power (Wats) 30W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (commercial) Efficiency Level VI Operating Temperature -20°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm x 33.6mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaRegion UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2.5APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Package	-
Form Wall Mount Input Type Fixed Blade, Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature -20°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm x 33.6mm)	Series	TE30
InnuitInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2.5APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature -20°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Form	Wall Mount
Voltage - Output12VCurrent - Output (Max)2.5APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Input Type	Fixed Blade, Multi-Blade (Sold Separately)
Current - Output (Max)2.5APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 53.0mm x 33.6mm)	Voltage - Output	12V
No Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Current - Output (Max)	2.5A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 33.6mm)	Power (Watts)	30W
ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	No Load Power Consumption	100mW (Max)
EfficiencyLevel VIOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Polarization	Positive Center
Operating Temperature -20°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Efficiency	Level VI
Size / Dimension 3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)	Operating Temperature	$-20^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Domost arres	Size / Dimension	3.78" L x 2.17" W x 1.32" H (96.0mm x 55.0mm x 33.6mm)
Kepon end		Report errors?

TE30A1203B01 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

TE30A1203B01 Payment Methods



If you have any question about TE30A1203B01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com