



## **TE500B68RJ Information**



For Reference Only

Part Number TE500B68RJ

Manufacturer TE Connectivity Passive Product

**Category** Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 68 OHM 5% 500W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **TE500B68RJ Specifications**

| Manufacturer Part NumberTE500B68RJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance68 OhmsTolerance±5%Power (Watts)500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.969" Dia x 12.441" L (50.00mm x 316.00mm) |                          |   |
|--|--------------------------|---|
| CategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance68 OhmsTolerance±5%Power (Watts)500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBrackets   | Manufacturer Part Number | TE500B68RJ                                  |
| Chassis Mount Resistors  Package Radial, Tubular  Series TE, CGS  Resistance 68 Ohms  Tolerance ±5%  Power (Watts) 500W  Composition Wirewound  Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets   | Manufacturer             | TE Connectivity Passive Product             |
| PackageRadial, TubularSeriesTE, CGSResistance68 OhmsTolerance±5%Power (Watts)500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBrackets  | Category                 | Resistors                                   |
| SeriesTE, CGSResistance68 OhmsTolerance±5%Power (Watts)500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBrackets  |                          | Chassis Mount Resistors                     |
| Resistance68 OhmsTolerance±5%Power (Watts)500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBrackets   | Package                  | Radial, Tubular                             |
| Tolerance ±5%  Power (Watts) 500W  Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  | Series                   | TE, CGS                                     |
| Power (Watts)       500W         Composition       Wirewound         Temperature Coefficient       ±440ppm/°C         Operating Temperature       -25°C ~ 225°C         Features       Flame Proof, Safety         Coating, Housing Type       Silicone Coated         Mounting Feature       Brackets   | Resistance               | 68 Ohms                                     |
| Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets   | Tolerance                | ±5%   |
| Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  | Power (Watts)            | 500W  |
| Operating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBrackets  | Composition              | Wirewound                                   |
| Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets   | Temperature Coefficient  | ±440ppm/°C                                  |
| Coating, Housing Type Silicone Coated  Mounting Feature Brackets   | Operating Temperature    | -25°C ~ 225°C                               |
| Mounting Feature Brackets  | Features                 | Flame Proof, Safety                         |
| -  | Coating, Housing Type    | Silicone Coated                             |
| Size / Dimension 1.969" Dia x 12.441" L (50.00mm x 316.00mm)   | Mounting Feature         | Brackets                                    |
|  | Size / Dimension         | 1.969" Dia x 12.441" L (50.00mm x 316.00mm) |
| Height - Seated (Max) -  | Height - Seated (Max)    | -   |
| Lead Style Solder Lugs   | Lead Style               | Solder Lugs                                 |
| Package / Case Radial, Tubular   | Package / Case           | Radial, Tubular                             |
| Failure Rate -   | Failure Rate             | -   |
| Report errors?   |                          | Report errors?                              |

#### **TE500B68RJ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **TE500B68RJ Payment Methods**



















### **TE500B68RJ Shipping Methods**













If you have any question about TE500B68RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com