



TE50B1K0J Information

Heisener.com

Part Number TE50B1K0J

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1K OHM 5% 50W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TE50B1K0J Specifications

Manufacturer Part NumberTE50B1KOJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance1 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBrackets
CategoryResistorsChassis Mount ResistorsPackageRadial, TubularSeriesTE, CGSResistance1 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone Coated
Chassis Mount Resistors Package Radial, Tubular Series TE, CGS Resistance 1 kOhms Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated
PackageRadial, TubularSeriesTE, CGSResistance1 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone Coated
SeriesTE, CGSResistance1 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone Coated
Resistance1 kOhmsTolerance $\pm 5\%$ Power (Watts) $50W$ CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/°C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$ FeaturesFlame Proof, SafetyCoating, Housing TypeSilicone Coated
Tolerance $\pm 5\%$ Power (Watts) $50W$ CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/°C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$ FeaturesFlame Proof, SafetyCoating, Housing TypeSilicone Coated
Power (Watts) $50W$ CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/°C}$ Operating Temperature $-25 ^{\circ}\text{C} \sim 225 ^{\circ}\text{C}$ FeaturesFlame Proof, SafetyCoating, Housing TypeSilicone Coated
CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/°C}$ Operating Temperature $-25 ^{\circ}\text{C} \sim 225 ^{\circ}\text{C}$ FeaturesFlame Proof, SafetyCoating, Housing TypeSilicone Coated
Temperature Coefficient $\pm 440 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$ Features Flame Proof, Safety Coating, Housing Type Silicone Coated
Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated
Features Flame Proof, Safety Coating, Housing Type Silicone Coated
Coating, Housing Type Silicone Coated
Mounting Feature Brackets
Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm)
Height - Seated (Max)
Lead Style Solder Lugs
Package / Case Radial, Tubular
Failure Rate -
Report errors's

TE50B1K0J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TE50B1K0J Payment Methods



















TE50B1K0J Shipping Methods













If you have any question about TE50B1K0J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com