



TE600B680RJ Information

Heisener.com

Part Number TE600B680RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 680 OHM 5% 600W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TE600B680RJ Specifications

Manufacturer Part NumberTE600B680RJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance680 OhmsTolerance±5%Power (Watts)600WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.575" Dia x 13.583" L (40.00mm x 345.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-			
Category Resistors Chassis Mount Resistors Package Radial, Tubular Series TE, CGS Resistance 680 Ohms Tolerance ±5% Power (Watts) 600W Composition Wirewound Temperature Coefficient 4440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Manufacturer Part Number	TE600B680RJ	
Chassis Mount Resistors Package Radial, Tubular TE, CGS Resistance 680 Ohms Tolerance ±5% Power (Watts) 600W Composition Wirewound Temperature Coefficient -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Manufacturer	TE Connectivity Passive Product	
Package Radial, Tubular Series TE, CGS Resistance 680 Ohms Tolerance ±5% Power (Watts) 600W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Category	Resistors	
SeriesTE, CGSResistance680 OhmsTolerance±5%Power (Watts)600WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.575" Dia x 13.583" L (40.00mm x 345.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors	
Resistance 680 Ohms Tolerance ±5% Power (Watts) 600W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Package	Radial, Tubular	
Tolerance ±5% Power (Watts) 600W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Series	TE, CGS	
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Resistance	680 Ohms	
Composition Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) - Lead Style Package / Case Radial, Tubular Failure Rate Wirewound #440ppm/°C -25°C ~ 225°C Flame Proof, Safety Silicone Coated #440ppm/°C #440ppm/°C -25°C ~ 225°C Flame Proof, Safety Silicone Coated #440ppm/°C #440ppm/°C	Tolerance	±5%	
Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Power (Watts)	600W	
Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Composition	Wirewound	
Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Temperature Coefficient	±440ppm/°C	
Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate Silicone Coated Brackets Solder Lugound Radial, Tubular	Operating Temperature	-25°C ~ 225°C	
Mounting Feature Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate Brackets Solder Lugs Radial, Tubular	Features	Flame Proof, Safety	
Size / Dimension 1.575" Dia x 13.583" L (40.00mm x 345.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Silicone Coated	
Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets	
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	1.575" Dia x 13.583" L (40.00mm x 345.00mm)	
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-	
Failure Rate -	Lead Style	Solder Lugs	
	Package / Case	Radial, Tubular	
Report errors?	Failure Rate	-	
		Report errors	?

TE600B680RJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TE600B680RJ Payment Methods



















TE600B680RJ Shipping Methods













If you have any question about TE600B680RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com