



TE60B18RJ Information

Heisener.com

Part Number TE60B18RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 18 OHM 5% 60W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TE60B18RJ Specifications

Manufacturer Part Number TE60B18RJ Manufacturer TE Connectivity Passive Product Category Resistors Package Radial, Tubular Series TE, CGS Resistance 18 Ohms Tolerance ±5% Power (Watts) 60W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	1200D10N3 Specifications	
CategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance18 OhmsTolerance±5%Power (Watts)60WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 4.016" L (28.00mm x 102.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	TE60B18RJ
Chassis Mount Resistors Package Radial, Tubular TE, CGS Resistance 18 Ohms Tolerance ±5% Power (Watts) 60W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - Chassis Mount Resistors Redial, Tubular Failure Rate - Chassis Mount Resistors TE, CGS Adial, Tubular Failure Rate - Coating, Housing Type Silicone Coated Autor (28.00mm x 102.00mm) Failure Rate - Chassis Mount Resistors TE, CGS Failure Rate Failure Rate - Chassis Mount Resistors TE, CGS Failure Rate Failure Rate Failure Rate - Chassis Mount Resistors TE, CGS Failure Rate Failure Rate Failure Rate Failure Rate Chassis Mount Resistors TE, CGS Failure Rate Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageRadial, TubularSeriesTE, CGSResistance18 OhmsTolerance±5%Power (Watts)60WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 4.016" L (28.00mm x 102.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesTE, CGSResistance18 OhmsTolerance±5%Power (Watts)60WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 4.016" L (28.00mm x 102.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance 18 Ohms Tolerance ±5% Power (Watts) 60W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 60W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Series	TE, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Package / Case Radial, Tubular Failure Rate -	Resistance	18 Ohms
Composition Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Package / Case Radial, Tubular Failure Rate Wirewound ±440ppm/°C -25°C ~ 225°C Flame Proof, Safety Silicone Coated Lead Style Brackets 1.102" Dia x 4.016" L (28.00mm x 102.00mm) - Radial, Tubular Failure Rate -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Power (Watts)	60W
Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Composition	Wirewound
Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type Silicone Coated Mounting Feature Brackets 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate Silicone Coated Brackets 1.102" Dia x 4.016" L (28.00mm x 102.00mm)	Operating Temperature	-25°C ~ 225°C
Mounting Feature Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate Brackets Solder L (28.00mm x 102.00mm) - Radial, Tubular - Radial, Tubular	Features	Flame Proof, Safety
Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Silicone Coated
Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	1.102" Dia x 4.016" L (28.00mm x 102.00mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

TE60B18RJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TE60B18RJ Payment Methods



















TE60B18RJ Shipping Methods













If you have any question about TE60B18RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com