



### **TE80B390RJ Information**

Heisener.com

Part Number TE80B390RJ

Manufacturer TE Connectivity Passive Product

**Category** Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 390 OHM 5% 80W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **TE80B390RJ Specifications**

Manufacturer Part NumberTE80B390RJManufacturerTE Connectivity Passive ProductCategoryResistorsChassis Mount ResistorsPackageRadial, TubularSeriesTE, CGSResistance390 OhmsTolerance±5%Power (Watts)80WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, Safety
Category  Resistors  Chassis Mount Resistors  Package  Radial, Tubular  Series  TE, CGS  Resistance  390 Ohms  Tolerance  ±5%  Power (Watts)  Romposition  Wirewound  Temperature Coefficient  ±440ppm/°C  Operating Temperature  -25°C ~ 225°C
Chassis Mount Resistors  Package Radial, Tubular  Series TE, CGS  Resistance 390 Ohms  Tolerance ±5%  Power (Watts) 80W  Composition Wirewound  Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C
PackageRadial, TubularSeriesTE, CGSResistance390 OhmsTolerance±5%Power (Watts)80WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°C
SeriesTE, CGSResistance $390 \text{ Ohms}$ Tolerance $\pm 5\%$ Power (Watts) $80W$ CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/°C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Resistance $390  \text{Ohms}$ Tolerance $\pm 5\%$ Power (Watts) $80W$ CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/°C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Tolerance $\pm 5\%$ Power (Watts) $80W$ CompositionWirewoundTemperature Coefficient $\pm 440 ppm/^{\circ}C$ Operating Temperature $-25^{\circ}C \sim 225^{\circ}C$
Power (Watts) $80W$ CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/°C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
CompositionWirewoundTemperature Coefficient $\pm 440 \text{ppm/°C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Temperature Coefficient $\pm 440 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Operating Temperature $-25^{\circ}\text{C} \sim 225^{\circ}\text{C}$
Features Flame Proof, Safety
Timber 1000, buttery
Coating, Housing Type Silicone Coated
Mounting Feature Brackets
Size / Dimension 1.102" Dia x 5.984" L (28.00mm x 152.00mm)
Height - Seated (Max)
Lead Style Solder Lugs
Package / Case Radial, Tubular
Failure Rate -
Report errors

#### **TE80B390RJ Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **TE80B390RJ Payment Methods**



















# **TE80B390RJ Shipping Methods**













If you have any question about TE80B390RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com