

TF3E227K010C0500

TF3E227K010C0500 Information

www.netsener.com	 TF3E227K010C0500 Vishay Sprague Capacitors Tantalum Capacitors CAP TANT 220UF 10V 10% 2917 2917 (7343 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



TF3E227K010C0500 Specifications

ManufacturerVishay SpragueCategoryCapacitorsTantalum CapacitorsPackage2917 (7343 Metric)SeriesTANTAMOUNT?, TF3Capacitance20µFColaracter±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-Voltage / Case2917 (7343 Metric)Stries Medication500 mOhmDeratage / Case2017 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in Fuse		
CategoryCapacitorsCategoryTantalum CapacitorsPackage2917 (7343 Metric)SeriesTANTAMOUNT?, TF3Capacitance220µFCapacitance220µFTolerance±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	Manufacturer Part Number	TF3E227K010C0500
Tantalum CapacitorsPackage2917 (7343 Metric)SeriesTANTAMOUNT?, TF3Capacitance220µFTolerance±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	Manufacturer	Vishay Sprague
Package2917 (7343 Metric)SeriesTANTAMOUNT?, TF3Capacitance220µFTolerance±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.169" (4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead SpacingEFeaturesFail Safe with Built-in FuseFailure Rate-	Category	Capacitors
YearTANTAMOUNT?, TF3Capacitance220µFTolerance±10%Voltage - Rated10VVoltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lad Spacing-FeaturesFail Safe with Built-in FuseFiglure Rate-		Tantalum Capacitors
Capacitance220µFTolerance±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-FeaturesFail Safe with Built-in FuseFeatures-	Package	2917 (7343 Metric)
Tolerance±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-FeaturesFail Safe with Built-in FuseFeatures-	Series	TANTAMOUNT?, TF3
Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFeatures-	Capacitance	220µF
TypeMoldedTypeS00 mOhmESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFeatures-	Tolerance	±10%
Ar500 mOhmESR (Equivalent Series Resistance)500 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	Voltage - Rated	10V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	Туре	Molded
Lifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	ESR (Equivalent Series Resistance)	500 mOhm
Mounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	Operating Temperature	-55°C ~ 125°C
Package / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	Lifetime @ Temp.	-
Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	Mounting Type	Surface Mount
Height - Seated (Max)0.169" (4.30mm)Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size CodeEFeaturesFail Safe with Built-in FuseFailure Rate-	Height - Seated (Max)	0.169" (4.30mm)
FeaturesFail Safe with Built-in FuseFailure Rate-	Lead Spacing	-
Failure Rate -	Manufacturer Size Code	Е
	Features	Fail Safe with Built-in Fuse
Report errors?	Failure Rate	-
		Report errors?

TF3E227K010C0500 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

TF3E227K010C0500 Payment Methods



If you have any question about TF3E227K010C0500, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com