



## **TFH85P1K50JE Information**

Heisener.com

Part Number TFH85P1K50JE

Manufacturer Ohmite
Category Resistors

Through Hole Resistors

**Description** RES 1.5K OHM 85W 5% TO264

Package TO-264-3, TO-264AA

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **TFH85P1K50JE Specifications**

Manufacturer Part Number         TFH85P1K50JE           Manufacturer         Ohmite           Category         Resistors           Through Hole Resistors           Package         TO-264-3, TO-264AA           Series         TFH           Resistance         1.5 kOhms           Tolerance         ±5%           Power (Watts)         85W           Composition         Thick Film           Features         Moisture Resistant, Non-Inductive           Temperature Coefficient         ±50ppm/°C           Operating Temperature         -           Package / Case         TO-264-3, TO-264AA           Supplier Device Package         TO-264           Size / Dimension         0.790" L x 0.200" W (20.07mm x 5.08mm)           Height - Seated (Max)         1.030" (26.16mm)           Number of Terminations         3           Failure Rate         -	•	
Category  Resistors  Through Hole Resistors  Package  TO-264-3, TO-264AA  Series  TFH  Resistance  1.5 kOhms  Tolerance  ±5%  Power (Watts)  85W  Composition  Thick Film  Features  Moisture Resistant, Non-Inductive  Temperature Coefficient  ±50ppm/°C  Operating Temperature  - Package / Case  TO-264-3, TO-264AA  Supplier Device Package  TO-264  Size / Dimension  0.790" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max)  Number of Terminations  3  Failure Rate  -	Manufacturer Part Number	TFH85P1K50JE
Package         TO-264-3, TO-264AA           Series         TFH           Resistance         1.5 kOhms           Tolerance         ±5%           Power (Watts)         85W           Composition         Thick Film           Features         Moisture Resistant, Non-Inductive           Temperature Coefficient         ±50ppm/°C           Operating Temperature         -           Package / Case         TO-264-3, TO-264AA           Supplier Device Package         TO-264           Size / Dimension         0.790" L x 0.200" W (20.07mm x 5.08mm)           Height - Seated (Max)         1.030" (26.16mm)           Number of Terminations         3           Failure Rate         -	Manufacturer	Ohmite
Package TO-264-3, TO-264AA  Series TFH  Resistance 1.5 kOhms  Tolerance ±5%  Power (Watts) 85W  Composition Thick Film  Features Moisture Resistant, Non-Inductive  Temperature Coefficient ±50ppm/°C  Operating Temperature -  Package / Case TO-264-3, TO-264AA  Supplier Device Package TO-264  Size / Dimension 0.790" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max) 1.030" (26.16mm)  Number of Terminations 3  Failure Rate -	Category	Resistors
SeriesTFHResistance1.5 kOhmsTolerance±5%Power (Watts)85WCompositionThick FilmFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±50ppm/°COperating Temperature-Package / CaseTO-264-3, TO-264AASupplier Device PackageTO-264Size / Dimension0.790" L x 0.200" W (20.07mm x 5.08mm)Height - Seated (Max)1.030" (26.16mm)Number of Terminations3Failure Rate-		Through Hole Resistors
Resistance 1.5 kOhms  Tolerance ±5%  Power (Watts) 85W  Composition Thick Film  Features Moisture Resistant, Non-Inductive  Temperature Coefficient ±50ppm/°C  Operating Temperature -  Package / Case TO-264-3, TO-264AA  Supplier Device Package TO-264  Size / Dimension 0.790" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max) 1.030" (26.16mm)  Number of Terminations 3  Failure Rate -	Package	TO-264-3, TO-264AA
Tolerance ±5%  Power (Watts) 85W  Composition Thick Film  Features Moisture Resistant, Non-Inductive  Temperature Coefficient ±50ppm/°C  Operating Temperature -  Package / Case TO-264-3, TO-264AA  Supplier Device Package TO-264  Size / Dimension 0.790" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max) 1.030" (26.16mm)  Number of Terminations 3  Failure Rate -	Series	TFH
Power (Watts)  Composition  Thick Film  Features  Moisture Resistant, Non-Inductive  ±50ppm/°C  Operating Temperature  Package / Case  TO-264-3, TO-264AA  Supplier Device Package  Size / Dimension  O.790" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max)  Number of Terminations  Failure Rate  -	Resistance	1.5 kOhms
Composition  Thick Film  Features  Moisture Resistant, Non-Inductive  ±50ppm/°C  Operating Temperature  - Package / Case  TO-264-3, TO-264AA  Supplier Device Package  TO-264  Size / Dimension  O.790" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max)  Number of Terminations  Failure Rate  -	Tolerance	±5%
Features  Moisture Resistant, Non-Inductive  ±50ppm/°C  Operating Temperature  - Package / Case  TO-264-3, TO-264AA  Supplier Device Package  TO-264  Size / Dimension  Or90" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max)  Number of Terminations  Failure Rate  -	Power (Watts)	85W
Temperature Coefficient ±50ppm/°C  Operating Temperature - Package / Case TO-264-3, TO-264AA  Supplier Device Package TO-264  Size / Dimension 0.790" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max) 1.030" (26.16mm)  Number of Terminations 3  Failure Rate -	Composition	Thick Film
Operating Temperature  Package / Case  TO-264-3, TO-264AA  Supplier Device Package  TO-264  Size / Dimension  O.790" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max)  Number of Terminations  3  Failure Rate  -	Features	Moisture Resistant, Non-Inductive
Package / Case TO-264-3, TO-264AA Supplier Device Package TO-264 Size / Dimension 0.790" L x 0.200" W (20.07mm x 5.08mm) Height - Seated (Max) 1.030" (26.16mm) Number of Terminations 3 Failure Rate -	Temperature Coefficient	±50ppm/°C
Supplier Device Package  TO-264 Size / Dimension  0.790" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max)  Number of Terminations  3 Failure Rate  -	Operating Temperature	-
Size / Dimension 0.790" L x 0.200" W (20.07mm x 5.08mm)  Height - Seated (Max) 1.030" (26.16mm)  Number of Terminations 3  Failure Rate -	Package / Case	TO-264-3, TO-264AA
Height - Seated (Max)  Number of Terminations  Failure Rate  1.030" (26.16mm)  3  Failure Rate	Supplier Device Package	TO-264
Number of Terminations 3 Failure Rate -	Size / Dimension	0.790" L x 0.200" W (20.07mm x 5.08mm)
Failure Rate -	Height - Seated (Max)	1.030" (26.16mm)
	Number of Terminations	3
Danort arrang?	Failure Rate	-
Report errors?		Report errors?

#### **TFH85P1K50JE Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **TFH85P1K50JE Payment Methods**





















## **TFH85P1K50JE Shipping Methods**













If you have any question about TFH85P1K50JE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com