



TL104K10R0CE Information

Heisener.com

Part Number TL104K10R0CE

Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 10 OHM 10% 158W

Package Modula

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TL104K10R0CE Specifications

Manufacturer Part Number TL104K10R0CE Manufacturer Ohmite Category Resistors Package Modular Series TL Resistance 10 Ohms Tolerance ±10% Power (Watts) 158W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -		
CategoryResistorsPackageModularSeriesTLResistance10 OhmsTolerance±10%Power (Watts)158WCompositionThick FilmTemperature Coefficient±250ppm/°COperating Temperature-40°C ~ 125°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.094" L x 1.012" W (104.00mm x 25.70mm)Height - Seated (Max)-Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-	Manufacturer Part Number	TL104K10R0CE
Package Modular Series TL Resistance 10 Ohms Tolerance ±10% Power (Watts) 158W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Manufacturer	Ohmite
Package Modular Series TL Resistance 10 Ohms Tolerance ±10% Power (Watts) 158W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Category	Resistors
Series TL Resistance 10 Ohms Tolerance ±10% Power (Watts) 158W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -		Chassis Mount Resistors
Resistance10 OhmsTolerance±10%Power (Watts)158WCompositionThick FilmTemperature Coefficient±250ppm/°COperating Temperature-40°C ~ 125°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.094" L x 1.012" W (104.00mm x 25.70mm)Height - Seated (Max)-Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-	Package	Modular
Tolerance ±10% Power (Watts) 158W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Series	TL
Power (Watts) Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Resistance	10 Ohms
Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Tolerance	±10%
Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Power (Watts)	158W
Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Composition	Thick Film
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate	Temperature Coefficient	±250ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Operating Temperature	-40°C ~ 125°C
Mounting Feature Flanges Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Features	-
Size / Dimension 4.094" L x 1.012" W (104.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Mounting Feature	Flanges
Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-	Size / Dimension	4.094" L x 1.012" W (104.00mm x 25.70mm)
Package / Case Modular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Quick Connects, 0.250" (6.35mm)
	Package / Case	Modular
Report errors?	Failure Rate	-
		Report errors?

TL104K10R0CE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TL104K10R0CE Payment Methods





















TL104K10R0CE Shipping Methods













If you have any question about TL104K10R0CE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com