

TL3240F100G Information



For Reference Only

Part Number TL3240F100G
Manufacturer E-Switch
Category Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TL3240F100G Specifications

Manufacturer Part Number TL3240F100G Manufacturer E-Switch Category Switches Package - Series TL3240 Circuit SPST-NO Switch Function Off-Mom Concat Rating @ Voltage 0.05A @ 12VDC Actuator Type Plunger for Cap Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.80mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.10mm x 6.10mm Illumination Illuminated Illumination Type, Color LED, Green Illumination Voltage (Nominal) 2 VDC Operating Force 100gf Ingress Protection - Features Board Guide		
Category Switches Package - Series TL3240 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Plunger for Cap Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.80mm Actuator Corientation Top Actuated Termination Style Gull Wing Outline 6.10mm x 6.10mm Illumination Illuminated Illumination Type, Color LED, Green Illumination Voltage (Nominal) 2 VDC Operating Force 100gf Ingress Protection - Features Board Guide	Manufacturer Part Number	TL3240F100G
Package - TL3240 Series TL3240 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Plunger for Cap Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.80mm Actuator Length, Right Angle - Top Actuated Termination Style Gull Wing Outline 6.10mm x 6.10mm Illumination Illuminated Illumination Type, Color LED, Green Illumination Voltage (Nominal) 2 VDC Operating Force 100gf Ingress Protection - Features Board Guide	Manufacturer	E-Switch
Package-SeriesTL3240CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypePlunger for CapMounting TypeSurface MountActuator Height off PCB, Vertical7.80mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.10mm x 6.10mmIlluminationIlluminatedIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCOperating Force100gfIngress Protection-FeaturesBoard Guide	Category	Switches
Series TL3240 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Plunger for Cap Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.80mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.10mm x 6.10mm Illumination Illuminated Illumination Type, Color LED, Green Illumination Voltage (Nominal) 2 VDC Operating Force 100gf Ingress Protection - Features Board Guide		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypePlunger for CapMounting TypeSurface MountActuator Height off PCB, Vertical7.80mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.10mm x 6.10mmIlluminationIlluminatedIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCOperating Force100gfIngress Protection-FeaturesBoard Guide	Package	-
Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Plunger for Cap Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.80mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.10mm x 6.10mm Illumination Illuminated Illumination Type, Color LED, Green Illumination Voltage (Nominal) 2 VDC Operating Force 100gf Ingress Protection - Features Board Guide	Series	TL3240
Contact Rating @ Voltage Actuator Type Plunger for Cap Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline Gull Wing Outline G.10mm x 6.10mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features D.05A @ 12VDC Plunger for Cap Plunger for Cap Plunger for Cap Surface Mount Gamma Surface Mount G.80mm Top Actuated Tup Actuated Top Actuated Top Actuated Top Actuated Tup Actuated Top Actuated To	Circuit	SPST-NO
Actuator Type Plunger for Cap Mounting Type Surface Mount Actuator Height off PCB, Vertical 7.80mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.10mm x 6.10mm Illumination Illuminated Illumination Type, Color LED, Green Illumination Voltage (Nominal) 2 VDC Operating Force 100gf Ingress Protection - Features Board Guide	Switch Function	Off-Mom
Mounting TypeSurface MountActuator Height off PCB, Vertical7.80mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.10mm x 6.10mmIlluminationIlluminatedIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCOperating Force100gfIngress Protection-FeaturesBoard Guide	Contact Rating @ Voltage	0.05A @ 12VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.10mm x 6.10mm Illumination Illumination Illuminated Illumination Type, Color LED, Green Illumination Voltage (Nominal) 2 VDC Operating Force 100gf Ingress Protection Features Board Guide	Actuator Type	Plunger for Cap
Actuator Length, Right Angle Actuator Orientation Top Actuated Gull Wing Outline 6.10mm x 6.10mm Illumination Illuminated Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.10mm x 6.10mm Illumination Illuminated Illumination Type, Color LED, Green Illumination Voltage (Nominal) 2 VDC Operating Force 100gf Ingress Protection - Features Board Guide	Actuator Height off PCB, Vertical	7.80mm
Termination Style Outline 6.10mm x 6.10mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Gull Wing 6.10mm x 6.10mm LED, Green 1lluminated LED, Green 100gf 100gf Board Guide	Actuator Length, Right Angle	-
Outline 6.10mm x 6.10mm Illumination Illuminated Illumination Type, Color LED, Green Illumination Voltage (Nominal) 2 VDC Operating Force 100gf Ingress Protection - Features Board Guide	Actuator Orientation	Top Actuated
IlluminationIlluminatedIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCOperating Force100gfIngress Protection-FeaturesBoard Guide	Termination Style	Gull Wing
Illumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCOperating Force100gfIngress Protection-FeaturesBoard Guide	Outline	6.10mm x 6.10mm
Illumination Voltage (Nominal)2 VDCOperating Force100gfIngress Protection-FeaturesBoard Guide	Illumination	Illuminated
Operating Force 100gf Ingress Protection - Features Board Guide	Illumination Type, Color	LED, Green
Ingress Protection - Board Guide	Illumination Voltage (Nominal)	2 VDC
Features Board Guide	Operating Force	100gf
	Ingress Protection	-
Report errors?	Features	Board Guide
		Report errors?

TL3240F100G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TL3240F100G Payment Methods





















TL3240F100G Shipping Methods













If you have any question about TL3240F100G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com