



TL3301NF100QG Information

Heisener.com

Part Number TL3301NF100QG

Manufacturer E-Switch

Category Switches
Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TL3301NF100QG Specifications

Manufacturer Part Number TL3301NF100QG Manufacturer E-Switch Category Switches Package - Series TL3301 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 4.30mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 100gf Ingress Protection - Features - Report errors?		
Category Switches Package - Series TL3301 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 4.30mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 100gf Ingress Protection - Features -	Manufacturer Part Number	TL3301NF100QG
Package - TL3301 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 4.30mm Actuator Length, Right Angle - Top Actuated Termination Style Gull Wing Outline 6.00mm x 6.00mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 100gf Ingress Protection - Features	Manufacturer	E-Switch
Package - Series TL3301 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 4.30mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 100gf Ingress Protection - Features -	Category	Switches
Series TL3301 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 4.30mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 100gf Ingress Protection - Features -		Tactile Switches
Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 4.30mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 100gf Ingress Protection - Features -	Package	-
Switch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical4.30mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.00mm x 6.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force100gfIngress Protection-Features-	Series	TL3301
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Gull Wing Outline G.00mm x 6.00mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.05A @ 12VDC Standard Standard Standard Standard Standard Standard Actuator Orientation Anguette G.00mm Actuator Orientation Top Actuated Gull Wing Outline 6.00mm x 6.00mm Illumination Illumination Illumination Illumination Illumination Illumination Illumination Voltage (Nominal) - Features	Circuit	SPST-NO
Actuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical4.30mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.00mm x 6.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force100gfIngress Protection-Features-	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Surface Mount 4.30mm 4.00mm Command Actuator Mon-Actuated Full Wing Gull Wing 6.00mm x 6.00mm Non-Illuminated	Contact Rating @ Voltage	0.05A @ 12VDC
Actuator Height off PCB, Vertical 4.30mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.00mm x 6.00mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 100gf Ingress Protection - Features - 4.30mm 4.3mm 4.30mm 4.3mm 4.3mm 4.3mm 4.3mm 4.3mm	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Gull Wing Outline 6.00mm x 6.00mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 100gf Ingress Protection - Features Features Top Actuated Top Actuated 100gf 100mm x 6.00mm x 6.00mm Non-Illuminated	Actuator Height off PCB, Vertical	4.30mm
Termination Style Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Gull Wing 6.00mm x 6.00mm Non-Illuminated - 100gf 100gf - 100gf - 100gf	Actuator Length, Right Angle	-
Outline 6.00mm x 6.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 100gf Ingress Protection - Features	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force100gfIngress Protection-Features-	Termination Style	Gull Wing
Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Outline	6.00mm x 6.00mm
Illumination Voltage (Nominal)-Operating Force100gfIngress Protection-Features-	Illumination	Non-Illuminated
Operating Force 100gf Ingress Protection - Features -	Illumination Type, Color	-
Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	100gf
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

TL3301NF100QG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TL3301NF100QG Payment Methods



















TL3301NF100QG Shipping Methods













If you have any question about TL3301NF100QG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com