



TL3305AF160QG Information

Part Number TL3305AF160QG

Manufacturer E-Switch **Category** Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 50MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TL3305AF160QG Specifications

Manufacturer Part Number TL.3305AF160QG Manufacturer E-Switch Category Switches Package - Series TL.3305 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.80mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -		
Category Switches Package - Series TL3305 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.80mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Fore 160gf Ingress Protection - Features -	Manufacturer Part Number	TL3305AF160QG
Package - TL3305 Series TL3305 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.80mm Actuator Length, Right Angle - Top Actuated Termination Style Gull Wing Outline 4.50mm x 4.50mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features - Series Actuator Indicated - Series	Manufacturer	E-Switch
Package - Series TL3305 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.80mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -	Category	Switches
Series TL3305 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.80mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical3.80mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline4.50mm x 4.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Package	-
Switch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical3.80mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline4.50mm x 4.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Series	TL3305
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Gull Wing Outline Gull Wing Outline Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.05A @ 12VDC Standard Standard Standard Standard Standard Standard Standard Surface Mount 3.80mm Top Actuated Gull Wing Gull Wing 4.50mm x 4.50mm Non-Illuminated Illumination Illumination Type, Color Illumination Voltage (Nominal) - Coperating Force I60gf Ingress Protection - Features	Circuit	SPST-NO
Actuator Type Surface Mount Actuator Height off PCB, Vertical 3.80mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.50mm x 4.50mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features - Surface Mount 3.80mm - Top Actuated Fundamental Style - Fundamental Surface Mount A.50mm x 4.50mm Top Actuated - Top Actuated - Top Actuated - Illumination Style Gull Wing - Gull Wing - 1.60gf - Features - Features - - - - - - - - - - - - -	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Gull Wing Outline Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Surface Mount 3.80mm Actuator Mount Top Actuated Gull Wing Gull Wing Outline 4.50mm x 4.50mm Non-Illuminated - 160gf 160gf Ingress Protection - Features	Contact Rating @ Voltage	0.05A @ 12VDC
Actuator Height off PCB, Vertical 3.80mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.50mm x 4.50mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Gull Wing Outline 4.50mm x 4.50mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features	Actuator Height off PCB, Vertical	3.80mm
Termination Style Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Gull Wing 4.50mm x 4.50mm Non-Illuminated - Ingress Protection - Ingress Protection - Features	Actuator Length, Right Angle	-
Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Termination Style	Gull Wing
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Outline	4.50mm x 4.50mm
Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Illumination	Non-Illuminated
Operating Force 160gf Ingress Protection - Features -	Illumination Type, Color	-
Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	160gf
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

TL3305AF160QG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TL3305AF160QG Payment Methods





















TL3305AF160QG Shipping Methods













If you have any question about TL3305AF160QG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com