



TL3330AF260QG Information



For Reference Only

Part Number TL3330AF260QG

Manufacturer E-Switch
Category Switches
Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TL3330AF260QG Specifications

| Manufacturer Part Number TL3330AF260QG Manufacturer E-Switch Category Switches Package - Series TL3330 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Rectangular Button Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle 3.50mm Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.90mm x 3.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features - | | |
|--|-----------------------------------|----------------------------|
| CategorySwitchesPackage-SeriesTL3330CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeRectangular ButtonMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle3.50mmActuator OrientationSide ActuatedTermination StyleGull WingOutline6.90mm x 3.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-Features- | Manufacturer Part Number | TL3330AF260QG |
| Package - Series TL3330 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Rectangular Button Mounting Type Surface Mount, Right Angle - Surface Mount, Right Angle - Side Actuator Height off PCB, Vertical - Actuator Length, Right Angle 3.50mm Actuator Length, Right Angle 3.50mm Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.90mm x 3.40mm Illumination Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Seatures - Surface Mount, Right Angle - Sur | Manufacturer | E-Switch |
| Package - Series TL3330 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Rectangular Button Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Height Angle 3.50mm Actuator Length, Right Angle 3.50mm Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.90mm x 3.40mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features | Category | Switches |
| SeriesTL3330CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeRectangular ButtonMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle3.50mmActuator OrientationSide ActuatedTermination StyleGull WingOutline6.90mm x 3.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-Features- | | Tactile Switches |
| Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Rectangular Button Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle 3.50mm Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.90mm x 3.40mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features - Features - | Package | - |
| Switch Function Contact Rating @ Voltage Actuator Type Rectangular Button Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Side Actuated Termination Style Gull Wing Outline G.90mm x 3.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Off-Mom Onf-Mom Rectangular Button Surface Mount, Right Angle - Surface Mount, Right An | Series | TL3330 |
| Contact Rating @ Voltage Actuator Type Rectangular Button Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Side Actuated Termination Style Gull Wing Outline G.90mm x 3.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.05A @ 12VDC Rectangular Button 8 cutator 9 cutator Rectangular Button Surface Mount, Right Angle - 8 doubt Angle - 8 doubt Actuated - 8 cutated - 9 cull Wing | Circuit | SPST-NO |
| Actuator Type Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle 3.50mm Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.90mm x 3.40mm Illumination Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 1260gf Ingress Protection Features Rectangular Button Rectangular Suplem Angle Rectangular Suplem A | Switch Function | Off-Mom |
| Mounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle3.50mmActuator OrientationSide ActuatedTermination StyleGull WingOutline6.90mm x 3.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-Features- | Contact Rating @ Voltage | 0.05A @ 12VDC |
| Actuator Height off PCB, Vertical Actuator Length, Right Angle 3.50mm Actuator Orientation Side Actuated Gull Wing Outline 6.90mm x 3.40mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force 1.00perating Force Tentures | Actuator Type | Rectangular Button |
| Actuator Length, Right Angle Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.90mm x 3.40mm Illumination Illumination Won-Illuminated Illumination Type, Color | Mounting Type | Surface Mount, Right Angle |
| Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.90mm x 3.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Features Side Actuated Gull Wing 6.90mm x 3.40mm 6.90mm x | Actuator Height off PCB, Vertical | - |
| Termination Style Outline 6.90mm x 3.40mm Illumination Non-Illuminated Illumination Type, Color | Actuator Length, Right Angle | 3.50mm |
| Outline 6.90mm x 3.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features | Actuator Orientation | Side Actuated |
| IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-Features- | Termination Style | Gull Wing |
| Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-Features- | Outline | 6.90mm x 3.40mm |
| Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-Features- | Illumination | Non-Illuminated |
| Operating Force260gfIngress Protection-Features- | Illumination Type, Color | - |
| Ingress Protection - Features - | Illumination Voltage (Nominal) | - |
| Features - | Operating Force | 260gf |
| | Ingress Protection | - |
| Report errors? | Features | - |
| | | Report errors? |

TL3330AF260QG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TL3330AF260QG Payment Methods



















TL3330AF260QG Shipping Methods













If you have any question about TL3330AF260QG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com