



# **TL6700NF160QG Information**

w Zom

For Reference Only

Part Number TL6700NF160QG

Manufacturer E-Switch
Category Switches
Tactile Switches

SWITCH TACTILE SPST-NO 0.05A 12V

Package

**Description** 

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **TL6700NF160QG Specifications**

Manufacturer Part Number         TL6700NF160QG           Manufacturer         E-Switch           Category         Switches           Package         -           Series         TL6700           Circuit         SPST-NO           Switch Function         Off-Mom           Cotact Rating @ Voltage         0.05A @ 12VDC           Actuator Type         Flush           Mounting Type         Surface Mount           Actuator Height off PCB, Vertical         2.60mm           Actuator Length, Right Angle         -           Actuator Orientation         Top Actuated           Termination Style         Gull Wing           Outline         6.90mm x 6.20mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         160gf           Ingress Protection         -           Features         Process Sealed		
Category         Switches           Package         -           Series         TL6700           Circuit         SPST-NO           Switch Function         Off-Mom           Contact Rating @ Voltage         0.05A @ 12VDC           Actuator Type         Flush           Mounting Type         Surface Mount           Actuator Height off PCB, Vertical         2.60mm           Actuator Length, Right Angle         -           Actuator Orientation         Top Actuated           Termination Style         Gull Wing           Outline         6.90mm x 6.20mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         160gf           Ingress Protection         -           Features         Process Sealed	Manufacturer Part Number	TL6700NF160QG
Package         -           Series         TL6700           Circuit         SPST-NO           Switch Function         Off-Mom           Contact Rating @ Voltage         0.05A @ 12VDC           Actuator Type         Flush           Mounting Type         Surface Mount           Actuator Height off PCB, Vertical         2.60mm           Actuator Length, Right Angle         -           Actuator Orientation         Top Actuated           Termination Style         Gull Wing           Outline         6.90mm x 6.20mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         160gf           Ingress Protection         -           Features         Process Sealed	Manufacturer	E-Switch
Package         -           Series         TL6700           Circuit         SPST-NO           Switch Function         Off-Mom           Contact Rating @ Voltage         0.05A @ 12VDC           Actuator Type         Flush           Mounting Type         Surface Mount           Actuator Height off PCB, Vertical         2.60mm           Actuator Length, Right Angle         -           Actuator Orientation         Top Actuated           Termination Style         Gull Wing           Outline         6.90mm x 6.20mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         160gf           Ingress Protection         -           Features         Process Sealed	Category	Switches
Series         TL6700           Circuit         SPST-NO           Switch Function         Off-Mom           Contact Rating @ Voltage         0.05A @ 12VDC           Actuator Type         Flush           Mounting Type         Surface Mount           Actuator Height off PCB, Vertical         2.60mm           Actuator Length, Right Angle         -           Actuator Orientation         Top Actuated           Termination Style         Gull Wing           Outline         6.90mm x 6.20mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         160gf           Ingress Protection         -           Features         Process Sealed		Tactile Switches
Circuit         SPST-NO           Switch Function         Off-Mom           Contact Rating @ Voltage         0.05A @ 12VDC           Actuator Type         Flush           Mounting Type         Surface Mount           Actuator Height off PCB, Vertical         2.60mm           Actuator Length, Right Angle         -           Actuator Orientation         Top Actuated           Termination Style         Gull Wing           Outline         6.90mm x 6.20mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         160gf           Ingress Protection         -           Features         Process Sealed	Package	-
Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Flush Mounting Type Surface Mount Actuator Height off PCB, Vertical 2.60mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features Process Sealed	Series	TL6700
Contact Rating @ Voltage Actuator Type Flush Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline Gull Wing Outline G.90mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features  0.05A @ 12VDC Flush Flush Flush Flush Flush Surface Mount Surface Mount Actuator Orientation C.60mm Actuator Orientation Top Actuated C.60mm Top Actuated C.690mm x 6.20mm Non-Illuminated Illumination Flush Fl	Circuit	SPST-NO
Actuator Type Surface Mount  Actuator Height off PCB, Vertical 2.60mm  Actuator Length, Right Angle -  Actuator Orientation Top Actuated  Termination Style Gull Wing  Outline 6.90mm x 6.20mm  Illumination Type, Color -  Illumination Voltage (Nominal) -  Operating Force 160gf  Ingress Protection -  Features Process Sealed	Switch Function	Off-Mom
Mounting TypeSurface MountActuator Height off PCB, Vertical2.60mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.90mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-FeaturesProcess Sealed	Contact Rating @ Voltage	0.05A @ 12VDC
Actuator Height off PCB, Vertical  Actuator Length, Right Angle  - Actuator Orientation  Top Actuated  Termination Style  Gull Wing  Outline  6.90mm x 6.20mm  Illumination  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force  Ingress Protection  Features  2.60mm  Actuator Operating Pocess Sealed	Actuator Type	Flush
Actuator Length, Right Angle  Actuator Orientation  Top Actuated  Gull Wing  Outline  6.90mm x 6.20mm  Illumination  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force  Ingress Protection  Features	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features Process Sealed	Actuator Height off PCB, Vertical	2.60mm
Termination Style  Outline  6.90mm x 6.20mm  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force  Ingress Protection  Features  Gull Wing  6.90mm x 6.20mm  Non-Illuminated  -  Ingress Sealed	Actuator Length, Right Angle	-
Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features Process Sealed	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-FeaturesProcess Sealed	Termination Style	Gull Wing
Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Outline	6.90mm x 6.20mm
Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-FeaturesProcess Sealed	Illumination	Non-Illuminated
Operating Force160gfIngress Protection-FeaturesProcess Sealed	Illumination Type, Color	-
Ingress Protection Features Process Sealed	Illumination Voltage (Nominal)	-
Features Process Sealed	Operating Force	160gf
	Ingress Protection	-
Report errors?	Features	Process Sealed
		Report errors?

### **TL6700NF160QG Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### TL6700NF160QG Payment Methods



















## TL6700NF160QG Shipping Methods













If you have any question about TL6700NF160QG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com