



TL88K75R0 Information



For Reference Only

Part Number TL88K75R0
Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 75 OHM 10% 114W

Package Modular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TL88K75R0 Specifications

Manufacturer Part Number TL88K75R0 Manufacturer Ohmite Category Resistors Package Modular Series TL Resistance 75 Ohms Tolerance ±10% Power (Watts) 114W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -		
Category Resistors Package Modular Series TL Resistance 75 Ohms Tolerance ±10% Power (Watts) 114W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Manufacturer Part Number	TL88K75R0
PackageModularSeriesTLResistance75 OhmsTolerance±10%Power (Watts)114WCompositionThick FilmTemperature Coefficient±250ppm/°COperating Temperature-40°C ~ 125°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.465" L x 1.012" W (88.00mm x 25.70mm)Height - Seated (Max)-Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-	Manufacturer	Ohmite
Package Modular Series TL Resistance 75 Ohms Tolerance ±10% Power (Watts) 114W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Category	Resistors
Series TL Resistance 75 Ohms Tolerance ±10% Power (Watts) 114W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -		Chassis Mount Resistors
Resistance 75 Ohms Tolerance ±10% Power (Watts) 114W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Package	Modular
Tolerance ±10% Power (Watts) 114W Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Series	TL
Power (Watts)114WCompositionThick FilmTemperature Coefficient±250ppm/°COperating Temperature-40°C ~ 125°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.465" L x 1.012" W (88.00mm x 25.70mm)Height - Seated (Max)-Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-	Resistance	75 Ohms
Composition Thick Film Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Tolerance	±10%
Temperature Coefficient ±250ppm/°C Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Power (Watts)	114W
Operating Temperature -40°C ~ 125°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Composition	Thick Film
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate	Temperature Coefficient	±250ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Operating Temperature	-40°C ~ 125°C
Mounting Feature Flanges Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Features	-
Size / Dimension 3.465" L x 1.012" W (88.00mm x 25.70mm) Height - Seated (Max) - Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Modular Failure Rate -	Mounting Feature	Flanges
Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseModularFailure Rate-	Size / Dimension	3.465" L x 1.012" W (88.00mm x 25.70mm)
Package / Case Modular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Quick Connects, 0.250" (6.35mm)
	Package / Case	Modular
Report errors?	Failure Rate	-
		Report errors?

TL88K75R0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TL88K75R0 Payment Methods



















TL88K75R0 Shipping Methods













If you have any question about TL88K75R0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com