



### **TLC072CP Information**



For Reference Only

Part Number TLC072CP

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

**Buffer Amps** 

**Description** IC OPAMP GP 10MHZ 8DIP **Package** 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **TLC072CP Specifications**

Manufacturer Part NumberTLC072CPManufacturerTexas InstrumentsCategoryIntegrated Circuits (ICs)Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-DIP (0.300", 7.62mm)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate19 V/μsGain Bandwidth Product10MHz-3db Bandwidth-Current - Input Bias1.5pAVoltage - Input Offset390μVCurrent - Supply2.1mACurrent - Output / Channel57mAVoltage - Supply, Single/Dual (±)4.5 V ~ 16 V, ±2.25 V ~ 8 V		
CategoryIntegrated Circuits (ICs)Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-DIP (0.300", 7.62mm)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate19 V/μsGain Bandwidth Product10MHz-3db Bandwidth-Current - Input Bias1.5pAVoltage - Input Offset390μVCurrent - Supply2.1mACurrent - Output / Channel57mAVoltage - Supply, Single/Dual (±)4.5 V ~ 16 V, ±2.25 V ~ 8 V	Manufacturer Part Number	TLC072CP
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Manufacturer	Texas Instruments
Package8-DIP (0.300", 7.62mm)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate19 V/μsGain Bandwidth Product10MHz-3db Bandwidth-Current - Input Bias1.5pAVoltage - Input Offset390μVCurrent - Supply2.1mACurrent - Output / Channel57mAVoltage - Supply, Single/Dual (±)4.5 V ~ 16 V, ±2.25 V ~ 8 V	Category	Integrated Circuits (ICs)
Series		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type General Purpose  Number of Circuits 2  Output Type - Slew Rate 19 V/ $\mu$ s  Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 1.5pA  Voltage - Input Offset 390 $\mu$ V  Current - Supply 2.1mA  Current - Output / Channel 57mA  Voltage - Supply, Single/Dual ( $\pm$ ) 4.5 V ~ 16 V, $\pm$ 2.25 V ~ 8 V	Package	8-DIP (0.300", 7.62mm)
Number of Circuits 2 Output Type - Slew Rate 19 V/ $\mu$ s Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390 $\mu$ V Current - Supply 2.1mA Current - Output / Channel 57mA Voltage - Supply, Single/Dual ( $\pm$ ) 4.5 V ~ 16 V, $\pm$ 2.25 V ~ 8 V	Series	-
Output Type - Slew Rate 19 V/ $\mu$ s Gain Bandwidth Product 10MHz - 3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390 $\mu$ V Current - Supply 2.1mA Current - Output / Channel 57mA Voltage - Supply, Single/Dual ( $\pm$ ) 4.5 V ~ 16 V, $\pm$ 2.25 V ~ 8 V	Amplifier Type	General Purpose
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Number of Circuits	2
Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390 $\mu$ V Current - Supply 2.1mA Current - Output / Channel 57mA Voltage - Supply, Single/Dual ( $\pm$ ) 4.5 V ~ 16 V, $\pm$ 2.25 V ~ 8 V	Output Type	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Slew Rate	19 V/μs
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Gain Bandwidth Product	10MHz
$Voltage - Input Offset \\ Supply \\ Current - Supply \\ Current - Output / Channel \\ Voltage - Supply, Single/Dual (±) \\ 4.5 \ V \sim 16 \ V, \pm 2.25 \ V \sim 8 \ V$	-3db Bandwidth	-
Current - Supply 2.1mA  Current - Output / Channel 57mA  Voltage - Supply, Single/Dual $(\pm)$ 4.5 V ~ 16 V, $\pm$ 2.25 V ~ 8 V	Current - Input Bias	1.5pA
Current - Output / Channel 57mA  Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V	Voltage - Input Offset	390μV
Voltage - Supply, Single/Dual ( $\pm$ ) 4.5 V ~ 16 V, $\pm$ 2.25 V ~ 8 V	Current - Supply	2.1mA
	Current - Output / Channel	57mA
	Voltage - Supply, Single/Dual (±)	4.5 V ~ 16 V, ±2.25 V ~ 8 V
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Operating Temperature	0°C ~ 70°C
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case 8-DIP (0.300", 7.62mm)	Package / Case	8-DIP (0.300", 7.62mm)
Supplier Device Package 8-PDIP	Supplier Device Package	8-PDIP
Report erro		Report errors?

### **TLC072CP Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **TLC072CP Payment Methods**





















### **TLC072CP Shipping Methods**













If you have any question about TLC072CP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com