



TLC074CD Information

westmeldener.com

For Reference Only

Part Number TLC074CD

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 10MHZ 14SOIC **Package** 14-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TLC074CD Specifications

Manufacturer Part Number TLC074CD Manufacturer Texas Instruments Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 14-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 19 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390μV Current - Supply 2.1mA Current - Output / Channel 57mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC		
Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps	Manufacturer Part Number	TLC074CD
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 14-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 19 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390μV Current - Supply 2.1mA Current - Output / Channel 57mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC	Manufacturer	Texas Instruments
Package 14-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 19 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390μV Current - Supply 2.1mA Current - Output / Channel 57mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 19 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390μV Current - Supply 2.1mA Current - Output / Channel 57mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type Number of Circuits 4 Output Type - Slew Rate 19 V/μs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset 390μV Current - Supply 2.1mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	14-SOIC (0.154", 3.90mm Width)
Number of Circuits 4 Output Type - Slew Rate 19 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390μV Current - Supply 2.1mA Current - Output / Channel 57mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC	Series	-
Output Type Slew Rate 19 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390µV Current - Supply 2.1mA Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package	Amplifier Type	General Purpose
Slew Rate Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390μV Current - Supply 2.1mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC	Number of Circuits	4
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 1.5pA Voltage - Input Offset 390µV Current - Supply 2.1mA Current - Output / Channel 57mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package	Output Type	-
$-3 db \ Bandwidth \\ Current - Input \ Bias \\ Voltage - Input \ Offset \\ 390 \mu V \\ Current - Supply \\ 2.1 mA \\ Current - Output / Channel \\ 57 mA \\ Voltage - Supply, Single/Dual (\pm) 4.5 \ V \sim 16 \ V, \pm 2.25 \ V \sim 8 \ V \\ Operating \ Temperature \\ 0^{\circ}C \sim 70^{\circ}C \\ Mounting \ Type \\ Surface \ Mount \\ Package / Case \\ 14-SOIC (0.154", 3.90mm \ Width) \\ Supplier \ Device \ Package \\ 14-SOIC$	Slew Rate	19 V/μs
Current - Input Bias 1.5pA $ \begin{tabular}{llll} & & & & & & & & & & & & & & & & & $	Gain Bandwidth Product	10MHz
Voltage - Input Offset $390\mu V$ Current - Supply $2.1 mA$ Current - Output / Channel $57 mA$ Voltage - Supply, Single/Dual (\pm) $4.5 V \sim 16 V$, $\pm 2.25 V \sim 8 V$ Operating Temperature $0^{\circ}C \sim 70^{\circ}C$ Mounting Type Surface Mount Package / Case 14 -SOIC $(0.154^{\circ}, 3.90 mm \ Width)$ Supplier Device Package 14 -SOIC	-3db Bandwidth	-
Current - Supply 2.1mA Current - Output / Channel 57mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC	Current - Input Bias	1.5pA
Current - Output / Channel 57mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 16 V, ±2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC	Voltage - Input Offset	390μV
Voltage - Supply, Single/Dual (\pm) 4.5 V ~ 16 V, \pm 2.25 V ~ 8 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC	Current - Supply	2.1mA
Operating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case14-SOIC (0.154", 3.90mm Width)Supplier Device Package14-SOIC	Current - Output / Channel	57mA
Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC	Voltage - Supply, Single/Dual (±)	4.5 V ~ 16 V, ±2.25 V ~ 8 V
Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC	Operating Temperature	0°C ~ 70°C
Supplier Device Package 14-SOIC	Mounting Type	Surface Mount
	Package / Case	14-SOIC (0.154", 3.90mm Width)
D	Supplier Device Package	14-SOIC
Report errors		Report errors?

TLC074CD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TLC074CD Payment Methods



















TLC074CD Shipping Methods













If you have any question about TLC074CD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com