



TLC274AIN Information



For Reference Only

Part Number TLC274AIN

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 2.2MHZ 14DIP **Package** 14-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TLC274AIN Specifications

Manufacturer Part Number TLC274AIN Manufacturer Texas Instruments Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 14-DIP (0.300", 7.62mm) Series LinCMOS? Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 5.3 V/μs Gain Bandwidth Product 2.2MHz -3db Bandwidth - Current - Input Bias 0.7pA Voltage - Input Offset 900μV	
CategoryIntegrated Circuits (ICs)Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage14-DIP (0.300", 7.62mm)SeriesLinCMOS?Amplifier TypeGeneral PurposeNumber of Circuits4Output Type-Slew Rate5.3 V/μsGain Bandwidth Product2.2MHz-3db Bandwidth-Current - Input Bias0.7pA	
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 14-DIP (0.300", 7.62mm) Series LinCMOS? Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 5.3 V/µs Gain Bandwidth Product 2.2MHz -3db Bandwidth - Current - Input Bias 0.7pA	
Package14-DIP (0.300", 7.62mm)SeriesLinCMOS?Amplifier TypeGeneral PurposeNumber of Circuits4Output Type-Slew Rate5.3 V/μsGain Bandwidth Product2.2MHz-3db Bandwidth-Current - Input Bias0.7pA	
Series LinCMOS? Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 5.3 V/µs Gain Bandwidth Product 2.2MHz -3db Bandwidth - Current - Input Bias 0.7pA	
Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 5.3 V/µs Gain Bandwidth Product 2.2MHz -3db Bandwidth - Current - Input Bias 0.7pA	
Number of Circuits 4 Output Type - Slew Rate 5.3 V/μs Gain Bandwidth Product 2.2MHz -3db Bandwidth - Current - Input Bias 0.7pA	
Output Type Slew Rate 5.3 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias - 0.7pA	
Slew Rate 5.3 V/μs Gain Bandwidth Product 2.2MHz -3db Bandwidth - Current - Input Bias 0.7pA	
Gain Bandwidth Product 2.2MHz -3db Bandwidth - Current - Input Bias 0.7pA	
-3db Bandwidth - Current - Input Bias 0.7pA	
Current - Input Bias 0.7pA	
Voltage - Input Offset 900uV	
Voltage - Input Offset 900µV	
Current - Supply 3.8mA	
Current - Output / Channel 30mA	
Voltage - Supply, Single/Dual (\pm) 4 V ~ 16 V, \pm 2 V ~ 8 V	
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Mounting Type Through Hole	
Package / Case 14-DIP (0.300", 7.62mm)	
Supplier Device Package 14-PDIP	
Report er	ors?

TLC274AIN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TLC274AIN Payment Methods





















TLC274AIN Shipping Methods













If you have any question about TLC274AIN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com