

TMK063CG2R7CP-F

TMK063CG2R7CP-F Information



For Reference Only

Part Number TMK063CG2R7CP-F

Manufacturer Taiyo Yuden Category Capacitors

Ceramic Capacitors

Description CAP CER 2.7PF 25V NP0 0201

Package 0201 (0603 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TMK063CG2R7CP-F Specifications

Manufacturer Part Number TMK063CG2R7CP-F Manufacturer Taiyo Yuden Category Capacitors Package 0201 (0603 Metric) Scries M Capacitance 2.7pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0201 (0603 Metric) Series M Capacitance 2.7pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Manufacturer Part Number	TMK063CG2R7CP-F
Package 0201 (0603 Metric) Series M Capacitance 2.7pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Manufacturer	Taiyo Yuden
Package 0201 (0603 Metric) Series M Capacitance 2.7pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Category	Capacitors
Series M Capacitance 2.7pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 2.7pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Package	0201 (0603 Metric)
Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Series	M
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Capacitance	2.7pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Tolerance	±0.25pF
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Voltage - Rated	25V
Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	0201 (0603 Metric)
Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Size / Dimension	0.024" L x 0.012" W (0.60mm x 0.30mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.013" (0.33mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

TMK063CG2R7CP-F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TMK063CG2R7CP-F Payment Methods



















TMK063CG2R7CP-F Shipping Methods













If you have any question about TMK063CG2R7CP-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com