

TMK105ABJ474KV-F

TMK105ABJ474KV-F Information



For Reference Only

Part Number TMK105ABJ474KV-F

ManufacturerTaiyo YudenCategoryCapacitors

Ceramic Capacitors

Description CAP CER 0.47UF 25V X5R 0402

Package 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TMK105ABJ474KV-F Specifications

Manufacturer Part Number TMK105ABJ474KV-F Manufacturer Taiyo Yuden Category Capacitors Package 0402 (1005 Metric) Series M Capacitance 0.47µF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -		
Category Capacitors Package 0402 (1005 Metric) Series M Capacitance 0.47µF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Manufacturer Part Number	TMK105ABJ474KV-F
Package 0402 (1005 Metric) Series M Capacitance 0.47μF Tolerance ±10% Voltage - Rated 25 V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Manufacturer	Taiyo Yuden
Package 0402 (1005 Metric) Series M Capacitance 0.47µF Tolerance ±10% Voltage - Rated 25 V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Category	Capacitors
Series M Capacitance 0.47μF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -		Ceramic Capacitors
Capacitance 0.47μF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Package	0402 (1005 Metric)
Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features Ratings Applications General Purpose Failure Rate Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) Thickness (Max) 0.022" (0.55mm) Lead Spacing	Series	M
Voltage - Rated Z5V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing 25V X5R Applications - Strace - Surface Mounting Type Surface Mount, MLCC 0402 (1005 Metric) - Thickness (Max) - Thickness (Max) - -	Capacitance	0.47μF
Temperature Coefficient N5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing X5R Sion - Sion - Sion - Sion - Sion - Sion - Sion - Sion - S	Tolerance	±10%
Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Voltage - Rated	25V
Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Temperature Coefficient	X5R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Operating Temperature	-55°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Applications	General Purpose
Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Failure Rate	-
Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.022" (0.55mm) -	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.022" (0.55mm) Lead Spacing -	Size / Dimension	0.039" L x 0.020" W (1.00mm x 0.50mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.022" (0.55mm)
	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

TMK105ABJ474KV-F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TMK105ABJ474KV-F Payment Methods



















TMK105ABJ474KV-F Shipping Methods













If you have any question about TMK105ABJ474KV-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com