



TMK107F104ZA-T Information



For Reference Only

Part Number TMK107F104ZA-T

Manufacturer Taiyo Yuden Category Capacitors

Ceramic Capacitors

Description CAP CER 0.1UF 25V Y5V 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TMK107F104ZA-T Specifications

Manufacturer Part Number TMK107F104ZA-T Manufacturer Taiyo Yuden Category Capacitors Package 0603 (1608 Metric) Series M Capacitance 0.1µF Tolerance -20%, +80% Voltage - Rated 25V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)		
Category Capacitors Package 0603 (1608 Metric) Series M Capacitance 0.1µF Tolerance -20%, +80% Voltage - Rated 25V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Manufacturer Part Number	TMK107F104ZA-T
Package O603 (1608 Metric) Series M Capacitance 0.1μF Tolerance -20%, +80% Voltage - Rated 25V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Manufacturer	Taiyo Yuden
Package 0603 (1608 Metric) Series M Capacitance 0.1 μF Tolerance -20%, +80% Voltage - Rated 25 V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Category	Capacitors
Series M Capacitance 0.1μF Tolerance -20%, +80% Voltage - Rated 25V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)		Ceramic Capacitors
Capacitance 0.1µF Tolerance -20%, +80% Voltage - Rated 25V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Package	0603 (1608 Metric)
Tolerance -20%, +80% Voltage - Rated 25V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Series	M
Voltage - Rated25 VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.035" (0.90mm)	Capacitance	0.1μF
Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Tolerance	-20%, +80%
Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) Thickness (Max) 0.035" (0.90mm)	Voltage - Rated	25V
Features - General Purpose Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Temperature Coefficient	Y5V (F)
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Operating Temperature	-30°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Applications	General Purpose
Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Failure Rate	-
Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm)	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) - 0.035" (0.90mm)	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.035" (0.90mm)	Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)
	Height - Seated (Max)	-
Lead Spacing -	Thickness (Max)	0.035" (0.90mm)
	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

TMK107F104ZA-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TMK107F104ZA-T Payment Methods



















TMK107F104ZA-T Shipping Methods













If you have any question about TMK107F104ZA-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com