

TMPG06-27A/4 Information



For Reference Only

Part Number TMPG06-27A/4

Manufacturer Vishay Semiconductor Diodes Division

Category Circuit Protection

TVS - Diodes

Description TVS DIODE 23.1VWM 37.5VC MPG06

Package MPG06, Axial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TMPG06-27A/4 Specifications

Manufacturer Part Number Manufacturer Vishay Semiconductor Diodes Division Category Circuit Protection TVS - Diodes Package MPG06, Axial Series - Type Zener Unidirectional Channels I Bidirectional Channels I Bidirectional Channels - Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 25.7V Voltage - Clamping (Max) @ Ipp 37.5V Current - Peak Pulse (10/1000µs) 10.7A Power - Peak Pulse 400W Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Package / Case MPG06, Axial Penert errors? Penert errors?	•	
Category Circuit Protection TVS - Diodes Package MPG06, Axial Series - Type Zener Unidirectional Channels I Bidirectional Channels - Voltage - Reverse Standoff (Typ) 23.1V Voltage - Breakdown (Min) 25.7V Voltage - Clamping (Max) @ Ipp 37.5V Current - Peak Pulse (10/1000µs) 10.7A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package	Manufacturer Part Number	TMPG06-27A/4
TVS - Diodes Package MPG06, Axial Series - Type Zener Unidirectional Channels Bidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 23.1V Voltage - Breakdown (Min) 25.7V Voltage - Clamping (Max) @ Ipp 37.5V Current - Peak Pulse (10/1000µs) 10.7A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package	Manufacturer	Vishay Semiconductor Diodes Division
PackageMPG06, AxialSeries-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000μs)10.7APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 185°C (TJ)Mounting TypeThrough HolePackage / CaseMPG06, AxialSupplier Device PackageMPG06	Category	Circuit Protection
Series-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000μs)10.7APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 185°C (TJ)Mounting TypeThrough HolePackage / CaseMPG06, AxialSupplier Device PackageMPG06		TVS - Diodes
TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000μs)10.7APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 185°C (TJ)Mounting TypeThrough HolePackage / CaseMPG06, AxialSupplier Device PackageMPG06	Package	MPG06, Axial
Unidirectional Channels Bidirectional Channels - Voltage - Reverse Standoff (Typ) 23.1V Voltage - Breakdown (Min) 25.7V Voltage - Clamping (Max) @ Ipp 37.5V Current - Peak Pulse (10/1000µs) 10.7A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package MPG06	Series	-
Bidirectional Channels-Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000μs)10.7APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 185°C (TJ)Mounting TypeThrough HolePackage / CaseMPG06, AxialSupplier Device PackageMPG06	Туре	Zener
Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 25.7V Voltage - Clamping (Max) @ Ipp 37.5V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package	Unidirectional Channels	1
Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 37.5V Current - Peak Pulse (10/1000μs) 10.7A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000μs)10.7APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 185°C (TJ)Mounting TypeThrough HolePackage / CaseMPG06, AxialSupplier Device PackageMPG06	Voltage - Reverse Standoff (Typ)	23.1V
Current - Peak Pulse (10/1000µs) Power - Peak Pulse 400W Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package	Voltage - Breakdown (Min)	25.7V
Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package MPG06	Voltage - Clamping (Max) @ Ipp	37.5V
Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package MPG06	Current - Peak Pulse (10/1000µs)	10.7A
Applications Capacitance @ Frequency Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package MPG06	Power - Peak Pulse	400W
Capacitance @ Frequency Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package MPG06	Power Line Protection	No
Operating Temperature -65°C ~ 185°C (TJ) Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package MPG06	Applications	General Purpose
Mounting Type Through Hole Package / Case MPG06, Axial Supplier Device Package MPG06	Capacitance @ Frequency	-
Package / Case MPG06, Axial Supplier Device Package MPG06	Operating Temperature	-65°C ~ 185°C (TJ)
Supplier Device Package MPG06	Mounting Type	Through Hole
•	Package / Case	MPG06, Axial
Papart arrors?	Supplier Device Package	MPG06
Report errors:		Report errors?

TMPG06-27A/4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TMPG06-27A/4 Payment Methods



















TMPG06-27A/4 Shipping Methods













If you have any question about TMPG06-27A/4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com