

TN2-H-24V Information



For Reference Only

Part Number TN2-H-24V

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 1A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TN2-H-24V Specifications

Manufacturer Part NumberTN2-H-24VManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesTNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesTNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	TN2-H-24V
Package-SeriesTNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - Series TN Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Category	Relays
SeriesTNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	TN
Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	24VDC
Switching Voltage Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time Sealed - Fully Mounting Type Termination Style 125VAC, 110VDC - Max 18 VDC 2.4 VDC 3ms Sealed - Fully Through Hole PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style 2.4 VDC 3ms Features PC Pin	Switching Voltage	125VAC, 110VDC - Max
Operate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	18 VDC
Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	3ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	3ms
Termination Style PC Pin	Features	Sealed - Fully
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

TN2-H-24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TN2-H-24V Payment Methods



















TN2-H-24V Shipping Methods













If you have any question about TN2-H-24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com