

### **TN2-H-5V Information**



For Reference Only

Part Number TN2-H-5V

Manufacturer Panasonic Electric Works

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GENERAL PURPOSE DPDT 1A 5V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **TN2-H-5V Specifications**

Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Signal Relays, Up to 2 Amps  Package  - Series  TN  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  28.1 mA  Coil Voltage  SvDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  1A  Switching Voltage  125 VAC, 110 VDC - Max  Turn On Voltage (Min)  Operate Time  3 ms  Release Time  3 ms  Release Time  Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin  Report errors?		
CategoryRelaysPackage-SeriesTNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current28.1 mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	TN2-H-5V
Package-SeriesTNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current28.1mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - Series TN Relay Type General Purpose Coil Type Non Latching Coil Current 28.1mA Coil Voltage SVDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 3ms Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesTNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current28.1mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current28.1mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current28.1mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	TN
Coil Current 28.1mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 3ms Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 5VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 1A  Switching Voltage 125VAC, 110VDC - Max  Turn On Voltage (Max) 3.75 VDC  Turn Off Voltage (Min) 0.5 VDC  Operate Time 3ms  Release Time 3ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  3.75 VDC  Turn Off Voltage (Min)  Operate Time  3ms  Release Time  3ms  Release Time  Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Current	28.1mA
Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  3.75 VDC  Turn Off Voltage (Min)  0.5 VDC  Operate Time  3ms  Release Time  3ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Voltage	5VDC
Switching Voltage  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  Sealed - Fully  Mounting Type  Termination Style  125VAC, 110VDC - Max  3.75 VDC  0.5 VDC  3ms  Sealed - Fully  Through Hole  PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Sealed - Fully  Mounting Type  Termination Style  3.75 VDC  3.75 VDC  3.75 VDC  3.75 VDC  5.75	Contact Rating (Current)	1A
Turn Off Voltage (Min)  Operate Time  3ms  Release Time  3ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  O.5 VDC  3ms  Features  PC Pin	Switching Voltage	125VAC, 110VDC - Max
Operate Time 3ms Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	3.75 VDC
Release Time 3ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.5 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	3ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	3ms
Termination Style PC Pin	Features	Sealed - Fully
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **TN2-H-5V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **TN2-H-5V Payment Methods**



















## **TN2-H-5V Shipping Methods**













If you have any question about TN2-H-5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com