


# TNPW12101K21BEEN

### **TNPW12101K21BEEN Information**



Part Number	TNPW12101K21BEEN	
Manufacturer	Vishay Dale	
Category	Resistors Chip Resistor - Surface Mount	
Description	RES SMD 1.21K OHM 0.1% 1/3W 1210	
Package	1210 (3225 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

## **TNPW12101K21BEEN Specifications**

Manufacturer Part NumberTNPW12101K21BEENManufacturerVishay DaleCategoryResistorsChip Resistor - Surface MountPackage1210 (3225 Metric)SeriesTNPWResistance1.21 kOhmsTolerance±0.1%Power (Watts)0.333W, 1/3WCompositionThin FilmFeaturesAnti-Sulfur, Moisture ResistantPoperature Coefficient±25ppm°COperating Temperature55°C ~ 125°CPackage / Case1210 (3225 Metric)Supplier Device Package1210 (3225 Metric)Size / Dimension0.126° L x 0.096" W (3.20mm x 2.45mm)Height - Seated (Max)0.030" (0.75mm)Number of Terminations2		
CategoryResistorsChip Resistor - Surface MountPackage1210 (3225 Metric)SeriesTNPWResistance1.21 kOhmsTolerance±0.1%Power (Watts)0.333W, 1/3WCompositionThin FilmFeaturesAnti-Sulfur, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature1210 (3225 Metric)Supplier Device Package1210 (3225 Metric)Supplier Device Package1210Height - Seated (Max)0.030" (0.75mm)	Manufacturer Part Number	TNPW12101K21BEEN
Chip Resistor - Surface MountPackage1210 (3225 Metric)SeriesTNPWResistance1.21 kOhmsTolerance±0.1%Power (Watts)0.333W, 1/3WCompositionThin FilmFeaturesAnti-Sulfur, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126° L x 0.096° W (3.20mm x 2.45mm)Height - Seated (Max)0.030° (0.75mm)	Manufacturer	Vishay Dale
Package1210 (3225 Metric)SeriesTNPWResistance1.21 kOhmsTolerance±0.1%Power (Watts)0.333W, 1/3WCompositionThin FilmFeaturesAnti-Sulfur, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 125°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.096" W (3.20mm x 2.45mm)Height - Seated (Max)0.030" (0.75mm)	Category	Resistors
SeriesTNPWResistance1.21 kOhmsTolerance±0.1%Power (Watts)0.333W, 1/3WCompositionThin FilmFeaturesAnti-Sulfur, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature55°C ~ 125°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.096" W (3.20mm x 2.45mm)Height - Seated (Max)0.030" (0.75mm)		Chip Resistor - Surface Mount
Resistance1.21 kOhmsTolerance±0.1%Power (Watts)0.333W, 1/3WCompositionThin FilmFeaturesAnti-Sulfur, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 125°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.096" W (3.20mm x 2.45mm)Height - Seated (Max)0.030" (0.75mm)	Package	1210 (3225 Metric)
Tolerance±0.1%Power (Watts)0.333W, 1/3WCompositionThin FilmFeaturesAnti-Sulfur, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 125°CPackage / Case1210 (3225 Metric)Supplier Device Package0.126" L x 0.096" W (3.20mm x 2.45mm)Height - Seated (Max)0.030" (0.75mm)	Series	TNPW
Power (Watts)0.333W, 1/3WCompositionThin FilmFeaturesAnti-Sulfur, Moisture ResistantTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 125°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.096" W (3.20mm x 2.45mm)Height - Seated (Max)0.030" (0.75mm)	Resistance	1.21 kOhms
CompositionThin FilmFeaturesAnti-Sulfur, Moisture ResistantTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 125°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.096" W (3.20mm x 2.45mm)Height - Seated (Max)0.030" (0.75mm)	Tolerance	$\pm 0.1\%$
FeaturesAnti-Sulfur, Moisture ResistantTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 125°CPackage / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.096" W (3.20mm x 2.45mm)Height - Seated (Max)0.030" (0.75mm)	Power (Watts)	0.333W, 1/3W
Temperature Coefficient ±25pm/°C   Operating Temperature -55°C ~ 125°C   Package / Case 1210 (3225 Metric)   Supplier Device Package 1210   Size / Dimension 0.126" L x 0.096" W (3.20mm x 2.45mm)   Height - Seated (Max) 0.030" (0.75mm)	Composition	Thin Film
Operating Temperature   -55°C ~ 125°C     Package / Case   1210 (3225 Metric)     Supplier Device Package   1210     Size / Dimension   0.126" L x 0.096" W (3.20mm x 2.45mm)     Height - Seated (Max)   0.030" (0.75mm)	Features	Anti-Sulfur, Moisture Resistant
Package / Case1210 (3225 Metric)Supplier Device Package1210Size / Dimension0.126" L x 0.096" W (3.20mm x 2.45mm)Height - Seated (Max)0.030" (0.75mm)	Temperature Coefficient	±25ppm/°C
Supplier Device Package   1210     Size / Dimension   0.126" L x 0.096" W (3.20mm x 2.45mm)     Height - Seated (Max)   0.030" (0.75mm)	Operating Temperature	-55°C ~ 125°C
Size / Dimension   0.126" L x 0.096" W (3.20mm x 2.45mm)     Height - Seated (Max)   0.030" (0.75mm)	Package / Case	1210 (3225 Metric)
Height - Seated (Max) 0.030" (0.75mm)	Supplier Device Package	1210
•	Size / Dimension	0.126" L x 0.096" W (3.20mm x 2.45mm)
Number of Terminations 2	Height - Seated (Max)	0.030" (0.75mm)
	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

### **TNPW12101K21BEEN Guarantees**



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **TNPW12101K21BEEN Payment Methods**



If you have any question about TNPW12101K21BEEN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com