

TPCR106K010A1800

TPCR106K010A1800 Information



Part Number	TPCR106K010A1800	
Manufacturer	AVX Corporation	
Category	Capacitors Tantalum Capacitors	
Description	CAP TANT 10UF 10V 10% 0805	
Package	0805 (2012 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



TPCR106K010A1800 Specifications

ManufacturerAVX CorporationCategoryCapacitorsTantalum CapacitorsPackage0805 (2012 Metric)SeriesTACmicrochip?, TPCCapacitance10µFTolerance1010°Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)1.8 OhmOperating Temperature-Voltage / Case805 (2012 Metric)Kifetim @ TempNounting Type0805 (2012 Metric)Package / Case0805 (2012 Metric)Size / Dimension0.059° (1.50mm)Height - Seated (Max)0.059° (1.50mm)Lead Spacing-FacturesGeneral Purpose		
CategoryCapacitorsTantalum CapacitorsPackage0805 (2012 Metric)SeriesTACmicrochip?, TPCCapacitance10µFTolerance±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)1.8 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting Type0805 (2012 Metric)Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-FaturesGeneral PurposeFailure Rate.Failure Rate.	Manufacturer Part Number	TPCR106K010A1800
Antalum CapacitorsPackage0805 (2012 Metric)SeriesTACmicrochip?, TPCCapacitance10μFTolerance±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)1.8 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-FeaturesGeneral PurposeFailure Rate-	Manufacturer	AVX Corporation
Package0805 (2012 Metric)SeriesTACmicrochip?, TPCCapacitance10µFTolerance±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)1.8 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.059" (1.50mm)Height - Seated (Max)0.059" (1.50mm)Lad SpacingRFeaturesGeneral PurposeFailure Rate-Failure Rate-<	Category	Capacitors
YearTACmicrochip?, TPCCapacitance10µFTolerance±10%Voltage - Rated10VYopeMoldedESR (Equivalent Series Resistance)1.8 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.059" (1.50mm)Height - Seated (Max)0.059" (1.50mm)Lad Spacing-FeaturesGeneral PurposeFailure Rate-Failure Rate-Fa		Tantalum Capacitors
Capacitance10μFTolerance±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)1.8 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.059" (1.50mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-FaturesGeneral PurposeFature Rate-	Package	0805 (2012 Metric)
Tolerance±10%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)1.8 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-FeaturesGeneral PurposeFailure Rate-	Series	TACmicrochip?, TPC
Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)1.8 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	Capacitance	10µF
TypeMoldedTypeMoldedESR (Equivalent Series Resistance)1.8 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	Tolerance	±10%
Ar1.8 OhmESR (Equivalent Series Resistance)1.8 OhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	Voltage - Rated	10V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	Туре	Molded
Lifetime @ TempMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	ESR (Equivalent Series Resistance)	1.8 Ohm
Mounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	Operating Temperature	-55°C ~ 125°C
Package / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	Lifetime @ Temp.	-
Size / Dimension0.079" L x 0.053" W (2.00mm x 1.35mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	Mounting Type	Surface Mount
Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	Package / Case	0805 (2012 Metric)
Lead Spacing-Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	Size / Dimension	0.079" L x 0.053" W (2.00mm x 1.35mm)
Manufacturer Size CodeRFeaturesGeneral PurposeFailure Rate-	Height - Seated (Max)	0.059" (1.50mm)
FeaturesGeneral PurposeFailure Rate-	Lead Spacing	-
Failure Rate -	Manufacturer Size Code	R
	Features	General Purpose
Report errors?	Failure Rate	-
		Report errors?

TPCR106K010A1800 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

TPCR106K010A1800 Payment Methods



If you have any question about TPCR106K010A1800, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com