

### **TPS-25L Information**



For Reference Only

Part Number TPS-25L Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 25A 170VDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **TPS-25L Specifications**

Manufacturer Part NumberTPS-25LManufacturerEatonCategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesTelpower? TPSFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC170VResponse Time-ApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)			
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesTelpower? TPSFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC170VResponse Time-ApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Manufacturer Part Number	TPS-25L	
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series Telpower? TPS Fuse Type Cartridge Current Rating 25A Voltage Rating - AC Voltage Rating - DC 170V Response Time - Applications Telecom Features - Class - Approvals Cyerting Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Cylindrical, Blade Terminal (Bolt)  Cylindrical, Blade Terminal (Bolt)	Manufacturer	Eaton	
PackageCylindrical, Blade Terminal (Bolt)SeriesTelpower? TPSFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC170VResponse Time-ApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Category	Circuit Protection	
Series         Telpower? TPS           Fuse Type         Cartridge           Current Rating         25A           Voltage Rating - AC         -           Voltage Rating - DC         170V           Response Time         -           Applications         Telecom           Features         -           Class         -           Approvals         CE, UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         100kA           Mounting Type         Bolt Mount           Package / Case         Cylindrical, Blade Terminal (Bolt)           Size / Dimension         0.563" Dia x 0.874" L (14.30mm x 22.20mm)		Electrical, Specialty Fuses	
Fuse Type Cartridge Current Rating 25A Voltage Rating - AC - Voltage Rating - DC 170V Response Time - Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Canada AC  Cartridge  Cartridge  Cartridge  25A  CH CO CE, UR  CHONA  CE, UR  CE, UR  CE, UR  CUINA  CUINA  CYLINDRICA  CYLINDRICA  CYLINDRICA  CYLINDRICA  CYLINDRICA  CARTRIDGE  C	Package	Cylindrical, Blade Terminal (Bolt)	
Current Rating 25A  Voltage Rating - AC -  Voltage Rating - DC 170V  Response Time -  Applications Telecom  Features -  Class -  Approvals CE, UR  Operating Temperature -  Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Series	Telpower? TPS	
Voltage Rating - AC  Voltage Rating - DC  170V  Response Time  - Applications  Telecom  Features  - Class  - Approvals  CE, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  - Sizo / Dimension  - Control 170V	Fuse Type	Cartridge	
Voltage Rating - DC  Response Time - Applications Telecom  Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension  170V  170V  170V  170V  1810	Current Rating	25A	
Response Time - Gecom - Getting Temperature - Gettin	Voltage Rating - AC	-	
Applications Features - Class - Approvals Cperating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Telecom  Telecom  Telecom  Telecom  100  Bolt Mount  CE, UR  100  Bolt Mount  CUR  CYUR  CYU	Voltage Rating - DC	170V	
Features - Class - CE, UR  Approvals CE, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Response Time	-	
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Applications	Telecom	
Approvals  CE, UR  Operating Temperature  - Breaking Capacity @ Rated Voltage  100kA  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Features	-	
Operating Temperature  Breaking Capacity @ Rated Voltage  100kA  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Class	-	
Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Approvals	CE, UR	
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Operating Temperature	-	
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Breaking Capacity @ Rated Voltage	100kA	
Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Mounting Type	Bolt Mount	
	Package / Case	Cylindrical, Blade Terminal (Bolt)	
D	Size / Dimension	0.563" Dia x 0.874" L (14.30mm x 22.20mm)	
Report errors?		R	eport errors?

### **TPS-25L Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **TPS-25L Payment Methods**

































If you have any question about TPS-25L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com