

TPS-5 Information

in sener.c

For Reference Only

Part Number TPS-5 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 5A 170VDC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TPS-5 Specifications

Manufacturer Part NumberTPS-5ManufacturerEatonCategoryCircuit ProtectionBectrical, Specialty FusesPackageCartridge, Non-StandardSeriesTelpower? TPSFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC-Voltage Rating - DC170VResponse Time-ApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesTelpower? TPSFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC-Voltage Rating - DC170VResponse Time-ApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Manufacturer Part Number	TPS-5
Package Cartridge, Non-Standard Series Telpower? TPS Fuse Type Cartridge Current Rating 5A Voltage Rating - AC - Voltage Rating - DC 170V Response Time - Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension IElecom Series Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Manufacturer	Eaton
Package Cartridge, Non-Standard Series Telpower? TPS Fuse Type Cartridge Current Rating 5A Voltage Rating - AC - Voltage Rating - DC 170V Response Time - Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Category	Circuit Protection
SeriesTelpower? TPSFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC-Voltage Rating - DC170VResponse Time-ApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating5AVoltage Rating - AC-Voltage Rating - DC170VResponse Time-ApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time - Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 5A 170V 170V 170V 170V 180V	Series	Telpower? TPS
Voltage Rating - AC Voltage Rating - DC 170V Response Time - Applications Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Size / Dimension - 170V Telecom - Clecom - Clecom - Clecom - Ce, UR - CE, UR - CE, UR - Catrridge, Non-Standard Size / Dimension - Size / Dimension - Size / Dimension	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Telecom Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 170V 170V 170V 170V 170V 1800 - 1800 1	Current Rating	5A
Response Time Applications Telecom Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension - Clecom CE, UR - CE,	Voltage Rating - AC	-
Applications Features - Class - Approvals Ce, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Telecom - Helecom - H	Voltage Rating - DC	170V
Features - Class - CE, UR Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Response Time	-
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Applications	Telecom
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Approvals	CE, UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Mounting Type	Holder
· · · · · · · · · · · · · · · · · · ·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 0.874" L (14.30mm x 22.20mm)
		Report errors?

TPS-5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TPS-5 Payment Methods



















TPS-5 Shipping Methods













If you have any question about TPS-5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com