



TPS2216ADAPG4 Information



For Reference Only

Part Number TPS2216ADAPG4

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)

PMIC - Power Distribution Switches, Load Drivers

DescriptionIC DUAL PCMCIA PWR SW 32HTSSOP**Package**32-TSSOP (0.240", 6.10mm Width) Exposed Pad

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TPS2216ADAPG4 Specifications

Manufacturer Part Number TPS2216ADAPG4 Manufacturer Texas Instruments Category Integrated Circuits (ICs) Package 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Series - Switch Type PCMCIA Switch Number of Outputs 4 Ratio - Input:Output 1:1 Output Configuration High Side Output Type - Interface Serial Voltage - Load 3.3V, 5V, 12V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 750mA Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP		
Category Integrated Circuits (ICs) PMIC - Power Distribution Switches, Load Drivers Package 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Series - Switch Type PCMCIA Switch Number of Outputs 4 Ratio - Input:Output 1:1 Output Configuration High Side Output Type - Interface Serial Voltage - Load 3.3V, 5V, 12V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 750mA Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP	Manufacturer Part Number	TPS2216ADAPG4
PMIC - Power Distribution Switches, Load Drivers Package 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Series - Switch Type PCMCIA Switch Number of Outputs 4 Ratio - Input:Output 1:1 Output Configuration High Side Output Type - Interface Serial Voltage - Load 3.3V, 5V, 12V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 750mA Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP	Manufacturer	Texas Instruments
Package32-TSSOP (0.240", 6.10mm Width) Exposed PadSeries-Switch TypePCMCIA SwitchNumber of Outputs4Ratio - Input:Output1:1Output ConfigurationHigh SideOutput Type-InterfaceSerialVoltage - Load3.3V, 5V, 12VVoltage - Supply (Vcc/Vdd)Not RequiredCurrent - Output (Max)750mARds On (Typ)140 mOhmInput Type-FeaturesStatus FlagFault ProtectionCurrent Limiting (Fixed), Over TemperatureOperating Temperature-40°C ~ 70°C (TA)Package / Case32-TSSOP (0.240", 6.10mm Width) Exposed PadSupplier Device Package32-HTSSOP	Category	Integrated Circuits (ICs)
Series - Switch Type PCMCIA Switch Number of Outputs 4 Ratio - Input:Output 1:1 Output Configuration High Side Output Type - Interface Serial Voltage - Load 3.3V, 5V, 12V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 750mA Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP		PMIC - Power Distribution Switches, Load Drivers
Switch TypePCMCIA SwitchNumber of Outputs4Ratio - Input:Output1:1Output ConfigurationHigh SideOutput Type-InterfaceSerialVoltage - Load3.3V, 5V, 12VVoltage - Supply (Vcc/Vdd)Not RequiredCurrent - Output (Max)750mARds On (Typ)140 mOhmInput Type-FeaturesStatus FlagFault ProtectionCurrent Limiting (Fixed), Over TemperatureOperating Temperature-40°C ~ 70°C (TA)Package / Case32-TSSOP (0.240", 6.10mm Width) Exposed PadSupplier Device Package32-HTSSOP	Package	32-TSSOP (0.240", 6.10mm Width) Exposed Pad
Number of Outputs4Ratio - Input:Output1:1Output ConfigurationHigh SideOutput Type-InterfaceSerialVoltage - Load3.3V, 5V, 12VVoltage - Supply (Vcc/Vdd)Not RequiredCurrent - Output (Max)750mARds On (Typ)140 mOhmInput Type-FeaturesStatus FlagFault ProtectionCurrent Limiting (Fixed), Over TemperatureOperating Temperature-40°C ~ 70°C (TA)Package / Case32-TSSOP (0.240", 6.10mm Width) Exposed PadSupplier Device Package32-HTSSOP	Series	-
Ratio - Input:Output1:1Output ConfigurationHigh SideOutput Type-InterfaceSerialVoltage - Load3.3V, 5V, 12VVoltage - Supply (Vcc/Vdd)Not RequiredCurrent - Output (Max)750mARds On (Typ)140 mOhmInput Type-FeaturesStatus FlagFault ProtectionCurrent Limiting (Fixed), Over TemperatureOperating Temperature-40°C ~ 70°C (TA)Package / Case32-TSSOP (0.240", 6.10mm Width) Exposed PadSupplier Device Package32-HTSSOP	Switch Type	PCMCIA Switch
Output Configuration High Side Output Type - Interface Serial Voltage - Load 3.3V, 5V, 12V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 750mA Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package	Number of Outputs	4
Output Type - Interface Serial Voltage - Load 3.3V, 5V, 12V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 750mA Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP	Ratio - Input:Output	1:1
Interface Serial Voltage - Load 3.3V, 5V, 12V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 750mA Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP	Output Configuration	High Side
Voltage - Load 3.3V, 5V, 12V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 750mA Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package	Output Type	-
Voltage - Supply (Vcc/Vdd) Current - Output (Max) Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package	Interface	Serial
Current - Output (Max) Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package	Voltage - Load	3.3V, 5V, 12V
Rds On (Typ) 140 mOhm Input Type - Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP	Voltage - Supply (Vcc/Vdd)	Not Required
Input Type - Status Flag Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP	Current - Output (Max)	750mA
Features Status Flag Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP	Rds On (Typ)	140 mOhm
Fault Protection Current Limiting (Fixed), Over Temperature Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP	Input Type	-
Operating Temperature -40°C ~ 70°C (TA) Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP	Features	Status Flag
Package / Case 32-TSSOP (0.240", 6.10mm Width) Exposed Pad Supplier Device Package 32-HTSSOP	Fault Protection	Current Limiting (Fixed), Over Temperature
Supplier Device Package 32-HTSSOP	Operating Temperature	-40°C ~ 70°C (TA)
	Package / Case	32-TSSOP (0.240", 6.10mm Width) Exposed Pad
Report errors?	Supplier Device Package	32-HTSSOP
		Report errors?

TPS2216ADAPG4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TPS2216ADAPG4 Payment Methods



















TPS2216ADAPG4 Shipping Methods













If you have any question about TPS2216ADAPG4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com