



TPS2839PWPRG4 Information



Part Number TPS2839PWPRG4

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

DescriptionIC BUCK MOSFET DRIVER 16-HTSSOPPackage16-TSSOP (0.173", 4.40mm Width) Exposed Pad

For the pricing/inventory/lead time, please contact

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TPS2839PWPRG4 Specifications

Manufacturer Part Number Manufacturer Texas Instruments Category Integrated Circuits (ICs) PMIC - Gate Drivers Package 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 10 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature 40°C ~ 125°C (TJ) Mounting Type Package 16-TSSOP 16-HTSSOP		
Category Integrated Circuits (ICs) PMIC - Gate Drivers Package 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 10 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) 29V Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package	Manufacturer Part Number	TPS2839PWPRG4
Package 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 10 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) 4A, 4A Input Type Inverting High Side Voltage - Max (Bootstrap) 29V Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad	Manufacturer	Texas Instruments
Package 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 10 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) 4A, 4A Input Type Inverting High Side Voltage - Max (Bootstrap) 29V Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply10 V ~ 15 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)29VRise / Fall Time (Typ)65ns, 65nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case16-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package16-HTSSOP		PMIC - Gate Drivers
Driven Configuration Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 10 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package	Package	16-TSSOP (0.173", 4.40mm Width) Exposed Pad
Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 10 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature 40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package	Series	-
Number of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply10 V ~ 15 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)29VRise / Fall Time (Typ)65ns, 65nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case16-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package16-HTSSOP	Driven Configuration	Half-Bridge
Gate TypeN-Channel MOSFETVoltage - Supply10 V ~ 15 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)29VRise / Fall Time (Typ)65ns, 65nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case16-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package16-HTSSOP	Channel Type	Synchronous
Voltage - Supply Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package	Gate Type	N-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package	Voltage - Supply	10 V ~ 15 V
Input Type Inverting High Side Voltage - Max (Bootstrap) 29V Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package 16-HTSSOP	Logic Voltage - VIL, VIH	1V, 2V
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package	Current - Peak Output (Source, Sink)	4A, 4A
Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package 16-HTSSOP	Input Type	Inverting
Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package 16-HTSSOP	High Side Voltage - Max (Bootstrap)	29V
Mounting Type Surface Mount Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package 16-HTSSOP	Rise / Fall Time (Typ)	65ns, 65ns
Package / Case 16-TSSOP (0.173", 4.40mm Width) Exposed Pad Supplier Device Package 16-HTSSOP	Operating Temperature	-40°C ~ 125°C (TJ)
Supplier Device Package 16-HTSSOP	Mounting Type	Surface Mount
	Package / Case	16-TSSOP (0.173", 4.40mm Width) Exposed Pad
	Supplier Device Package	16-HTSSOP
Report errors?		Report errors?

TPS2839PWPRG4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TPS2839PWPRG4 Payment Methods





















TPS2839PWPRG4 Shipping Methods













If you have any question about TPS2839PWPRG4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com