

TPW-200

TPW-200 Information

Heisener.com	Part Number	TPW-200
	Manufacturer	Eaton
	Category	Circuit Protection Electrical, Specialty Fuses
	Description	FUSE RECTANGULR 200A 80VDC BLADE
	Package	Blade Type, Module
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

TPW-200 Specifications

ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageBlad Type, ModuleSeriesTelpower? TPWFuse TypeRectangularCurrent Rating200AVoltage Rating - AC80VVoltage Rating - DC80VResponse Time-ApplicationsFelecomFeaturesIndicatingApprovalsUROperating Temperature-Package/ Case100AAPackage / Case100AAPackage / Case100AAPackage / Case100AAPackage / Case100AAPackage / Case100APackage / Case100A<			
CategoryCircuit ProtectionElectrical, Specialty FusesPackageBlade Type, ModuleSeriesTelpower? TPWFuse TypeRectangularCurrent Rating200AVoltage Rating - AC-Voltage Rating - DC80VResponse Time-ApplicationsTelecomFeaturesIndicatingClass-ApprovalsUROperating Temperature100kABreaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" K x 1.455" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Manufacturer Part Number	TPW-200	
Electrical, Specialty FusesPackageBlade Type, ModuleSeriesTelpower? TPWFuse TypeRectangularCurrent Rating200AVoltage Rating - AC-Voltage Rating - DC80VResponse Time-ApplicationsTelecomFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Manufacturer	Eaton	
PackageBlade Type, ModuleSeriesTelpower? TPWFuse TypeRectangularFuse Type200ACurrent Rating200AVoltage Rating - AC-Voltage Rating - DC80VResponse Time-ApplicationsTelecomFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Category	Circuit Protection	
Series Telpower? TPW Fuse Type Rectangular Current Rating 200A Voltage Rating - AC - Voltage Rating - DC 80V Response Time - Applications Telecom Restarting - Approvals Indicating Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Bade Type, Module Size / Dimension 2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)		Electrical, Specialty Fuses	
Fuse Type Rectangular Current Rating 200A Voltage Rating - AC - Voltage Rating - DC 80V Response Time - Applications Telecom Features Indicating Class - Approvals UR Operating Temperature 100kA Breaking Capacity @ Rated Voltage 100kA Mounting Type Blade Type, Module Size / Dimension 2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Package	Blade Type, Module	
Current Rating200AVoltage Rating - AC-Voltage Rating - DC80VResponse Time-ApplicationsTelecomFeaturesIndicatingClass-ApprovalsUROperating Temperature100kABreaking Capacity @ Rated VoltageHolderMounting TypeBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 93.50mm)	Series	Telpower? TPW	
Voltage Rating - AC-Voltage Rating - DC80VResponse Time-ApplicationsTelecomFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 93.50mm)	Fuse Type	Rectangular	
Voltage Rating - DC80VResponse Time-ApplicationsTelecomFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Current Rating	200A	
Response Time-ApplicationsTelecomFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Voltage Rating - AC	-	
ApplicationsTelecomFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Voltage Rating - DC	80V	
FeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 93.50mm)	Response Time	-	
Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 93.50mm)	Applications	Telecom	
ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 93.50mm)	Features	Indicating	
Operating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 93.50mm)	Class	-	
Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Approvals	UR	
Mounting TypeHolderPackage / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Operating Temperature	-	
Package / CaseBlade Type, ModuleSize / Dimension2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Breaking Capacity @ Rated Voltage	100kA	
Size / Dimension 2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	Mounting Type	Holder	
	Package / Case	Blade Type, Module	
Report errors?	Size / Dimension	2.495" L x 1.459" W x 3.681" H (63.37mm x 37.06mm x 93.50mm)	
		Report errors?	

TPW-200 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about TPW-200, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com