

## **TQ2H-24V Information**



For Reference Only

Part Number TQ2H-24V

Manufacturer Panasonic Electric Works

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY TELECOM DPDT 1A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **TQ2H-24V Specifications**

Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Signal Relays, Up to 2 Amps  Package  - Series  TQ  Relay Type  Telecom  Coil Type  Non Latching  Coil Current  8.3mA  Coil Voltage  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  1A  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  3ms  Release Time  3ms  Release Time  3ms  Features  Mounting Type  Through Hole  Termination Style  PC Pin  Report errors?		
CategoryRelaysPackage-SeriesTQRelay TypeTelecomCoil TypeNon LatchingCoil Current8.3 mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	TQ2H-24V
Package-SeriesTQRelay TypeTelecomCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - TQ  Relay Type Telecom  Coil Type Non Latching  Coil Current 8.3mA  Coil Voltage 24VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 1A  Switching Voltage 125VAC, 110VDC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 3ms  Release Time 3ms  Features - Mounting Type Through Hole  Termination Style PC Pin	Category	Relays
SeriesTQRelay TypeTelecomCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	TQ
Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Relay Type	Telecom
Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  3ms  Release Time  3ms  Features  -  Mounting Type  Through Hole  Termination Style	Coil Current	8.3mA
Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  3ms  Release Time  3ms  Features  - Mounting Type  Through Hole  Termination Style	Coil Voltage	24VDC
Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  3ms  Release Time  3ms  Features  - Mounting Type  Through Hole  Termination Style	Contact Rating (Current)	1A
Turn Off Voltage (Min)  Operate Time  3ms  Release Time  3ms  Features  -  Mounting Type  Through Hole  Termination Style  2.4 VDC  3ms  Through Hole  PC Pin	Switching Voltage	125VAC, 110VDC - Max
Operate Time 3ms Release Time 3ms Features	Turn On Voltage (Max)	18 VDC
Release Time 3ms  Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	3ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	3ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

### **TQ2H-24V Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **TQ2H-24V Payment Methods**





















### **TQ2H-24V Shipping Methods**













If you have any question about TQ2H-24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com