



TRAPC8M1X Information

Heisener.com

Part Number TRAPC8M1X Manufacturer Switchcraft Inc.

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 8POS R/A MALE T/H

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TRAPC8M1X Specifications

Manufacturer Part Number TRAPC8M1X Manufacturer Switchcraft Inc. Category Connectors, Interconnects Package - Series Tini Q-G? TRAPC Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert Mini XLR Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Thermoplastic Contact Finish Tin Features Board Guide Voltage - Rated 125VAC Current Rating 1.5A		
CategoryConnectors, InterconnectsPackage-SeriesTini Q-G? TRAPCConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - InsertMini XLRShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishThermoplasticContact FinishTinFeaturesBoard GuideVoltage - Rated125VACCurrent Rating1.5A	Manufacturer Part Number	TRAPC8M1X
Package-SeriesTini Q-G? TRAPCConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - InsertMini XLRShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishThermoplasticContact FinishTinFeaturesBoard GuideVoltage - Rated125VACCurrent Rating1.5A	Manufacturer	Switchcraft Inc.
Package-SeriesTini Q-G? TRAPCConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - InsertMini XLRShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishThermoplasticContact FinishTinFeaturesBoard GuideVoltage - Rated125VACCurrent Rating1.5A	Category	Connectors, Interconnects
SeriesTini Q-G? TRAPCConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - InsertMini XLRShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishThermoplasticContact FinishTinFeaturesBoard GuideVoltage - Rated125VACCurrent Rating1.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - InsertMini XLRShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishThermoplasticContact FinishTinFeaturesBoard GuideVoltage - Rated125VACCurrent Rating1.5A	Package	-
Number of Positions8Shell Size - InsertMini XLRShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishThermoplasticContact FinishTinFeaturesBoard GuideVoltage - Rated125VACCurrent Rating1.5A	Series	Tini Q-G? TRAPC
Shell Size - InsertMini XLRShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishThermoplasticContact FinishTinFeaturesBoard GuideVoltage - Rated125VACCurrent Rating1.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Thermoplastic Contact Finish Tin Features Board Guide Voltage - Rated Current Rating 1.5A	Number of Positions	8
Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishThermoplasticContact FinishTinFeaturesBoard GuideVoltage - Rated125VACCurrent Rating1.5A	Shell Size - Insert	Mini XLR
Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Thermoplastic Contact Finish Tin Features Board Guide Voltage - Rated 125VAC Current Rating 1.5A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Thermoplastic Contact Finish Tin Features Board Guide Voltage - Rated 125VAC Current Rating 1.5A	Mounting Type	Through Hole, Right Angle
Orientation Keyed Ingress Protection - Shell Material, Finish Thermoplastic Contact Finish Tin Features Board Guide Voltage - Rated 125VAC Current Rating 1.5A	Termination	Solder
Ingress Protection - Shell Material, Finish Thermoplastic Contact Finish Tin Features Board Guide Voltage - Rated 125VAC Current Rating 1.5A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Tin Features Board Guide Voltage - Rated 125VAC Current Rating 1.5A	Orientation	Keyed
Contact Finish Features Board Guide Voltage - Rated 125VAC Current Rating 1.5A	Ingress Protection	-
Features Board Guide Voltage - Rated 125VAC Current Rating 1.5A	Shell Material, Finish	Thermoplastic
Voltage - Rated 125VAC Current Rating 1.5A	Contact Finish	Tin
Current Rating 1.5A	Features	Board Guide
	Voltage - Rated	125VAC
Report errors?	Current Rating	1.5A
		Report errors?

TRAPC8M1X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TRAPC8M1X Payment Methods





















TRAPC8M1X Shipping Methods













If you have any question about TRAPC8M1X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com