



TRC-075S500DT Information

Heisener.com

Part Number TRC-075S500DT

Manufacturer Thomas Research Products

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 7-15V 5A

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TRC-075S500DT Specifications

Manufacturer Part Number TRC-0758500DT Manufacturer Thomas Research Products Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series TRC-075 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 7 ~ 15 V Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series TRC-075 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 7 ~ 15 V Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Manufacturer Part Number	TRC-075S500DT	
Package - Series TRC-075 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 7 ~ 15 V Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Manufacturer	Thomas Research Products	
Package - Series TRC-075 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 7 ~ 15 V Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series TRC-075 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 7 ~ 15 V Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)		LED Drivers	
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 7 ~ 15 V Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Output (Max) 305VAC Voltage - Output (Max) 5A Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Series	TRC-075	
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 7 ~ 15 V Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Туре	Constant Current	
Voltage - Input (Min)90VACVoltage - Input (Max)305VACVoltage - Output7 ~ 15 VCurrent - Output (Max)5APower (Watts)75WVoltage - Isolation-DimmingAnalogFeaturesOCP, OTP, OVP, SCPRatingsIP67Operating Temperature-40°C ~ 70°CEfficiency87%Termination StyleWire LeadsSize / Dimension5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Topology	AC DC Converter	
Voltage - Input (Max)305VACVoltage - Output7 ~ 15 VCurrent - Output (Max)5APower (Watts)75WVoltage - Isolation-DimmingAnalogFeaturesOCP, OTP, OVP, SCPRatingsIP67Operating Temperature-40°C ~ 70°CEfficiency87%Termination StyleWire LeadsSize / Dimension5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Number of Outputs	1	
Voltage - Output 7 ~ 15 V Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Voltage - Input (Min)	90VAC	
Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Voltage - Input (Max)	305VAC	
Power (Watts) 75W Voltage - Isolation - Dimming Analog Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Voltage - Output	7 ~ 15 V	
Voltage - Isolation-DimmingAnalogFeaturesOCP, OTP, OVP, SCPRatingsIP67Operating Temperature-40°C ~ 70°CEfficiency87%Termination StyleWire LeadsSize / Dimension5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Current - Output (Max)	5A	
DimmingAnalogFeaturesOCP, OTP, OVP, SCPRatingsIP67Operating Temperature-40°C ~ 70°CEfficiency87%Termination StyleWire LeadsSize / Dimension5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Power (Watts)	75W	
Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Voltage - Isolation	-	
Ratings IP67 Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Dimming	Analog	
Operating Temperature -40°C ~ 70°C Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Features	OCP, OTP, OVP, SCP	
Efficiency 87% Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Ratings	IP67	
Termination Style Wire Leads Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Operating Temperature	-40°C ~ 70°C	
Size / Dimension 5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	Efficiency	87%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	5.91" L x 2.66" W x 1.44" H (150.0mm x 67.5mm x 36.5mm)	
			Report errors?

TRC-075S500DT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TRC-075S500DT Payment Methods



















TRC-075S500DT Shipping Methods













If you have any question about TRC-075S500DT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com