

TS4061AICT-1.25

Request a Quote

TS4061AICT-1.25 Information

www.heisen.nom	Part Number	TS4061AICT-1.25	
	Manufacturer	STMicroelectronics	
	Category	Integrated Circuits (ICs) PMIC - Voltage Reference	
	Description	IC VREF SHUNT 1.25V SOT323	
	Package	SC-70, SOT-323	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



TS4061AICT-1.25 Specifications

ManufacturerSTMicroelectronicsCategoryIntegrated Circuits (ICs)PackagePMIC - Voltage ReferencePackageSC-70, SOT-323Series-Reference TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)1.25VVoltage - Output (Max)-Current - Output15mATolerance±0.1%Tolerance10µVp-pNoise - 0.1Hz to 10Hz0µUp-pNoise - 10Hz to 10KHz95µVrmsVoltage - Input-Current - Supply-Current - Cathode12µAOperating Temperature12µAOperating TemperatureSurface MountAuding TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323		
Category Integrated Circuits (ICs) PMIC - Voltage Reference PMIC - Voltage Reference Package SC-70, SOT-323 Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 1.25V Voltage - Output (Max) - Current - Output 15mA Tolerance ±0.1% Tolerance ±0.1% Noise - 0.1Hz to 10Hz 10µVp-p Noise - 10Hz to 10Hz 95µVrms Voltage - Input - Current - Supply - Voltage - Input - Noise - 0.1Hz to 10Hz 95µVrms Voltage - Input - Current - Supply - Qurrent - Cathode 12µA Operating Temperature Surface Mount Package / Case SC-70, SOT-323 Supplier Device Package SUT-323	Manufacturer Part Number	TS4061AICT-1.25
PMIC - Voltage ReferencePackageSC-70, SOT-323Series-Reference TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)1.25VVoltage - Output (Max)-Current - Output15mATolerance±0.1%Tomperature Coefficient35ppm/°CNoise - 0.1Hz to 10Hz10µVp-pNoise - 10Hz to 10kHz95µVrmsVoltage - Input-Current - Supply-Current - Supply-Operating Temperature12µAOperating TemperatureSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Manufacturer	STMicroelectronics
PackageSC-70, SOT-323Series-Referenc TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)1.25VVoltage - Output (Max)-Current - Output15mATolerance±0.1%Tolerance10µVp-pNoise - 0.1Hz to 10Hz09µVrmsNoise - 10Hz to 10KHz95µVrmsVoltage - Input-Current - Supply-Current - Cathode12µAOperating Temperature40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Category	Integrated Circuits (ICs)
Series-Reference TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)1.25VVoltage - Output (Max)-Current - Output15mATolerance±0.1%Tolerance10µVp-pNoise - 0.1Hz to 10Hz09µVrnsNoise - 10Hz to 10kHz95µVrmsVoltage - Input-Current - Supply-Current - Cathode12µAOperating Temperature40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323		PMIC - Voltage Reference
Reference TypeShuntOutput TypeFixedOutput Qin/Fixed)1.25VVoltage - Output (Max)-Current - Output15mATolerance±0.1%Tolerance35ppm/°CNoise - 0.1Hz to 10Hz0µVp-pNoise - 10Hz to 10KHz95µVrmsVoltage - Input-Current - Supply-Operating Temperature40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Package	SC-70, SOT-323
Output Type Fixed Voltage - Output (Min/Fixed) 1.25V Voltage - Output (Max) - Current - Output 15mA Tolerance ±0.1% Temperature Coefficient 35ppm/°C Noise - 0.1Hz to 10Hz 10μVp-p Noise - 10Hz to 10kHz 95μVrms Voltage - Input - Current - Supply - Querating Temperature 12μA Operating Temperature Surface Mount Package / Case SC-70, SOT-323 Supplier Device Package SOT-323	Series	-
Voltage - Output (Min/Fixed) 1.25V Voltage - Output (Max) - Current - Output 15mA Tolerance ±0.1% Temperature Coefficient 35ppm/°C Noise - 0.1Hz to 10Hz 10µVp-p Noise - 10Hz to 10kHz 95µVrms Voltage - Input - Current - Supply - Current - Cathode 12µA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SC-70, SOT-323 Supplier Device Package SOT-323	Reference Type	Shunt
Voltage - Output (Max) - Current - Output 15mA Tolerance ±0.1% Temperature Coefficient 35ppm/°C Noise - 0.1Hz to 10Hz 10µVp-p Noise - 10Hz to 10kHz 95µVrms Voltage - Input - Current - Supply - Current - Cathode 12µA Operating Temperature Surface Mount Package / Case Surface Mount Supplier Device Package SOT-323	Output Type	Fixed
Current - Output15mATolerance±0.1%Temperature Coefficient35ppm/°CNoise - 0.1Hz to 10Hz10μVp-pNoise - 10Hz to 10Hz95μVrmsVoltage - Input-Current - Supply-Current - Cathode12μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Voltage - Output (Min/Fixed)	1.25V
Tolerance ±0.1% Temperature Coefficient 35pm/°C Noise - 0.1Hz to 10Hz 10μVp-p Noise - 10Hz to 10kHz 95μVrms Voltage - Input - Current - Supply - Current - Cathode 12μA Operating Temperature 40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SC-70, SOT-323 Supplier Device Package SOT-323	Voltage - Output (Max)	-
Temperature Coefficient35ppm/°CNoise - 0.1Hz to 10Hz10μVp-pNoise - 10Hz to 10kHz95μVrmsVoltage - Input-Current - Supply-Current - Cathode12μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Current - Output	15mA
Noise - 0.1Hz to 10Hz 10μVp-p Noise - 10Hz to 10kHz 95μVrms Voltage - Input - Current - Supply - Current - Cathode 12μA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SC-70, SOT-323 Supplier Device Package SOT-323	Tolerance	$\pm 0.1\%$
Noise - 10Hz to 10kHz95μVrmsVoltage - Input-Current - Supply-Current - Cathode12μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Temperature Coefficient	35ppm/°C
Voltage - Input - Current - Supply - Current - Cathode 12µA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SC-70, SOT-323 Supplier Device Package SOT-323	Noise - 0.1Hz to 10Hz	10µVp-p
Current - Supply-Current - Cathode12μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Noise - 10Hz to 10kHz	95µVrms
Current - Cathode12μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Voltage - Input	-
Operating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Current - Supply	-
Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Current - Cathode	12μΑ
Package / CaseSC-70, SOT-323Supplier Device PackageSOT-323	Operating Temperature	-40°C ~ 85°C (TA)
Supplier Device Package SOT-323	Mounting Type	Surface Mount
	Package / Case	SC-70, SOT-323
Perort errors?	Supplier Device Package	SOT-323
Report errors?		Report errors?

TS4061AICT-1.25 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

TS4061AICT-1.25 Payment Methods





If you have any question about TS4061AICT-1.25, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com