

### **TS6A1S08A Information**



For Reference Only

Part Number TS6A1S08A
Manufacturer APEM Inc.
Category Switches

Navigation Switches, Joystick

**Description** SWITCH THMBSTK PUSHBUTTON HALL

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **TS6A1S08A Specifications**

Manufacturer Part Number         TS6A1S08A           Manufacturer         APEM Inc.           Category         Switches           Package         -           Series         TS           Type         Thumbstick, 2 - Axis           Actuator Type         Pushbutton           Switch Function         4-Way Directional, Center Select           Functions, Extra         -           Output         Analog (Hall Effect)           Voltage - Supply         5VDC           Current Rating         -           Voltage Rating - AC         -           Voltage Rating - DC         -           Contact Material         -           Contact Finish         -           Mounting Type         Panel Mount           Termination Style         Wire Leads           Operating Temperature         -40°C ~ 85°C           Panel Cutout Dimensions         Circular - 25.65mm Dia           Ingress Protection         IP68/69K - Dust Tight, Water Resistant, Waterproof           Features         -           Report errors?	•		
Category         Switches           Navigation Switches, Joystick           Package         -           Series         TS           Type         Thumbstick, 2 - Axis           Actuator Type         Pushbutton           Switch Function         4-Way Directional, Center Select           Functions, Extra         -           Output         Analog (Hall Effect)           Voltage - Supply         5VDC           Current Rating         -           Voltage Rating - AC         -           Voltage Rating - DC         -           Contact Material         -           Contact Finish         -           Mounting Type         Panel Mount           Termination Style         Wire Leads           Operating Temperature         -40°C ~ 85°C           Panel Cutout Dimensions         Circular - 25.65mm Dia           Ingress Protection         IP68/69K - Dust Tight, Water Resistant, Waterproof           Features         -	Manufacturer Part Number	TS6A1S08A	
Package         -           Series         TS           Type         Thumbstick, 2 - Axis           Actuator Type         Pushbutton           Switch Function         4-Way Directional, Center Select           Functions, Extra         -           Output         Analog (Hall Effect)           Voltage - Supply         5VDC           Current Rating         -           Voltage Rating - AC         -           Voltage Rating - DC         -           Contact Material         -           Contact Finish         -           Mounting Type         Panel Mount           Termination Style         Wire Leads           Operating Temperature         -40°C ~ 85°C           Panel Cutout Dimensions         Circular - 25.65mm Dia           Ingress Protection         IP68/69K - Dust Tight, Water Resistant, Waterproof           Features         -	Manufacturer	APEM Inc.	
Package         -           Series         TS           Type         Thumbstick, 2 - Axis           Actuator Type         Pushbutton           Switch Function         4-Way Directional, Center Select           Functions, Extra         -           Output         Analog (Hall Effect)           Voltage - Supply         5VDC           Current Rating         -           Voltage Rating - AC         -           Voltage Rating - DC         -           Contact Material         -           Contact Finish         -           Mounting Type         Panel Mount           Termination Style         Wire Leads           Operating Temperature         -40°C ~ 85°C           Panel Cutout Dimensions         Circular - 25.65mm Dia           Ingress Protection         IP68/69K - Dust Tight, Water Resistant, Waterproof           Features         -	Category	Switches	
SeriesTSTypeThumbstick, 2 - AxisActuator TypePushbuttonSwitch Function4-Way Directional, Center SelectFunctions, Extra-OutputAnalog (Hall Effect)Voltage - Supply5VDCCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Contact Material-Contact Finish-Mounting TypePanel MountTermination StyleWire LeadsOperating Temperature-40°C ~ 85°CPanel Cutout DimensionsCircular - 25.65mm DiaIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofFeatures-		Navigation Switches, Joystick	
Type Thumbstick, 2 - Axis  Actuator Type Pushbutton  Switch Function 4-Way Directional, Center Select  Functions, Extra -  Output Analog (Hall Effect)  Voltage - Supply 5VDC  Current Rating -  Voltage Rating - AC -  Voltage Rating - DC -  Contact Material -  Contact Finish -  Mounting Type Panel Mount  Termination Style Wire Leads  Operating Temperature -40°C ~ 85°C  Panel Cutout Dimensions Circular - 25.65mm Dia  Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof  Features -  Tunned Contact Finish Functional Push Superproper Selection Features -  Tomber Style Function Style Function IP68/69K - Dust Tight, Water Resistant, Waterproof  Features -  Thumbstick, 2 - Axis  Pushbutton  4-Way Directional, Center Select  4-Way Direct	Package	-	
Actuator TypePushbuttonSwitch Function4-Way Directional, Center SelectFunctions, Extra-OutputAnalog (Hall Effect)Voltage - Supply5VDCCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Contact Material-Contact Finish-Mounting TypePanel MountTermination StyleWire LeadsOperating Temperature-40°C ~ 85°CPanel Cutout DimensionsCircular - 25.65mm DiaIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofFeatures-	Series	TS	
Switch Function 4-Way Directional, Center Select Functions, Extra - Output Analog (Hall Effect) Voltage - Supply 5VDC Current Rating - Voltage Rating - AC - Voltage Rating - DC - Contact Material - Contact Finish - Mounting Type Panel Mount Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Туре	Thumbstick, 2 - Axis	
Functions, Extra  Output  Analog (Hall Effect)  Voltage - Supply  5VDC  Current Rating  - Voltage Rating - AC  Voltage Rating - DC  Contact Material  Contact Finish  - Mounting Type  Panel Mount  Termination Style  Operating Temperature  -40°C ~ 85°C  Panel Cutout Dimensions  Ingress Protection  Features  - Analog (Hall Effect)	Actuator Type	Pushbutton	
Output Analog (Hall Effect)  Voltage - Supply 5VDC  Current Rating -  Voltage Rating - AC -  Voltage Rating - DC -  Contact Material -  Contact Finish -  Mounting Type Panel Mount  Termination Style Wire Leads  Operating Temperature -40°C ~ 85°C  Panel Cutout Dimensions Circular - 25.65mm Dia  Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof  Features -  Analog (Hall Effect)  5VDC  Wire  40°C ~ 85°C  Circular - 25.65mm Dia  IP68/69K - Dust Tight, Water Resistant, Waterproof  Features -	Switch Function	4-Way Directional, Center Select	
Voltage - Supply5VDCCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Contact Material-Contact Finish-Mounting TypePanel MountTermination StyleWire LeadsOperating Temperature-40°C ~ 85°CPanel Cutout DimensionsCircular - 25.65mm DiaIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofFeatures-	Functions, Extra	-	
Current Rating  Voltage Rating - AC  Voltage Rating - DC  Contact Material  Contact Finish  Mounting Type  Panel Mount  Termination Style  Operating Temperature  -40°C ~ 85°C  Panel Cutout Dimensions  Ingress Protection  IP68/69K - Dust Tight, Water Resistant, Waterproof  Features	Output	Analog (Hall Effect)	
Voltage Rating - AC  Voltage Rating - DC  Contact Material  Contact Finish  Mounting Type  Panel Mount  Termination Style  Operating Temperature  -40°C ~ 85°C  Panel Cutout Dimensions  Circular - 25.65mm Dia  Ingress Protection  IP68/69K - Dust Tight, Water Resistant, Waterproof  Features  -  Contact Material  -  -  -  -  -  -  -  -  -  -  -  -  -	Voltage - Supply	5VDC	
Voltage Rating - DC  Contact Material  Contact Finish  -  Mounting Type  Panel Mount  Termination Style  Wire Leads  Operating Temperature  -40°C ~ 85°C  Panel Cutout Dimensions  Circular - 25.65mm Dia  Ingress Protection  IP68/69K - Dust Tight, Water Resistant, Waterproof  Features  -  -  -  -  -  -  -  -  -  -  -  -  -	Current Rating	-	
Contact Material - Contact Finish - Mounting Type Panel Mount  Termination Style Wire Leads Operating Temperature -40°C ~ 85°C  Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Voltage Rating - AC	-	
Contact Finish  Mounting Type Panel Mount  Termination Style Wire Leads Operating Temperature -40°C ~ 85°C  Panel Cutout Dimensions Circular - 25.65mm Dia  Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof  Features -	Voltage Rating - DC	-	
Mounting Type Panel Mount  Termination Style Wire Leads  Operating Temperature -40°C ~ 85°C  Panel Cutout Dimensions Circular - 25.65mm Dia  Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof  Features -	Contact Material	-	
Termination Style Wire Leads  Operating Temperature -40°C ~ 85°C  Panel Cutout Dimensions Circular - 25.65mm Dia  Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof  Features -	Contact Finish	-	
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Mounting Type	Panel Mount	
Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Termination Style	Wire Leads	
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Operating Temperature	-40°C ~ 85°C	
Features -	Panel Cutout Dimensions	Circular - 25.65mm Dia	
	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof	
Report errors?	Features	-	
		Report	errors?

#### TS6A1S08A Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **TS6A1S08A Payment Methods**





















### **TS6A1S08A Shipping Methods**













If you have any question about TS6A1S08A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com