



TSDA2S02A Information



For Reference Only

Part Number TSDA2S02A Manufacturer APEM Inc. Category Switches

Navigation Switches, Joystick

Description SWITCH THUMBSTICK CONICAL HALL

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TSDA2S02A Specifications

| Manufacturer Part Number TSDA2S02A Manufacturer APEM Inc. Category Switches Navigation Switches, Joystick Package - Series TS Type Thumbstick, 2 - Axis Actuator Type Conical Switch Function 4-Way Directional Functions, Extra - Output Analog (Hall Effect) Voltage - Supply 5VDC Current Rating - Voltage Rating - AC - Voltage Rating - DC - Contact Material - Contact Finish - Mounting Type Panel Mount Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - Report errors? | • | |
|---|--------------------------|--|
| Category Switches Package - Series TS Type Thumbstick, 2 - Axis Actuator Type Conical Switch Function 4-Way Directional Functions, Extra - Output Analog (Hall Effect) Voltage - Supply 5VDC Current Rating - Voltage Rating - AC - Voltage Rating - DC - Contact Material - Contact Finish - Mounting Type Panel Mount Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | Manufacturer Part Number | TSDA2S02A |
| Package - Series TS Type Thumbstick, 2 - Axis Actuator Type Conical Switch Function 4-Way Directional Functions, Extra - Output Analog (Hall Effect) Voltage - Supply 5VDC Current Rating - Voltage Rating - AC - Voltage Rating - DC - Contact Material - Contact Finish - Mounting Type Panel Mount Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | Manufacturer | APEM Inc. |
| Package - Series TS Type Thumbstick, 2 - Axis Actuator Type Conical Switch Function 4-Way Directional Functions, Extra - Output Analog (Hall Effect) Voltage - Supply 5VDC Current Rating - Voltage Rating - AC - Voltage Rating - DC - Contact Material - Contact Finish - Mounting Type Panel Mount Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | Category | Switches |
| Series TS Type Thumbstick, 2 - Axis Actuator Type Conical Switch Function 4-Way Directional Functions, Extra - Output Analog (Hall Effect) Voltage - Supply 5VDC Current Rating - Voltage Rating - AC - Voltage Rating - DC - Contact Material - Contact Finish - Mounting Type Panel Mount Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | | Navigation Switches, Joystick |
| Type Conical Switch Function 4-Way Directional Functions, Extra - Output Analog (Hall Effect) Voltage - Supply 5VDC Current Rating - Voltage Rating - AC Voltage Rating - DC Contact Material - Contact Finish - Mounting Type Panel Mount Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection Features Conical Switch Function A- Conical Contact Finish - Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features | Package | - |
| Actuator TypeConicalSwitch Function4-Way DirectionalFunctions, Extra-OutputAnalog (Hall Effect)Voltage - Supply5VDCCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Contact Material-Contact Finish-Mounting TypePanel MountTermination StyleWire LeadsOperating Temperature-40°C ~ 85°CPanel Cutout DimensionsCircular - 25.65mm DiaIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofFeatures- | Series | TS |
| Switch Function4-Way DirectionalFunctions, Extra-OutputAnalog (Hall Effect)Voltage - Supply5VDCCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Contact Material-Contact Finish-Mounting TypePanel MountTermination StyleWire LeadsOperating Temperature-40°C ~ 85°CPanel Cutout DimensionsCircular - 25.65mm DiaIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofFeatures- | Туре | Thumbstick, 2 - Axis |
| Functions, Extra Output Analog (Hall Effect) Voltage - Supply 5VDC Current Rating - Voltage Rating - AC Voltage Rating - DC - Contact Material Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Ingress Protection Features - Analog (Hall Effect) - Analog (Hall Effect) | Actuator Type | Conical |
| OutputAnalog (Hall Effect)Voltage - Supply5VDCCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Contact Material-Contact Finish-Mounting TypePanel MountTermination StyleWire LeadsOperating Temperature-40°C ~ 85°CPanel Cutout DimensionsCircular - 25.65mm DiaIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofFeatures- | Switch Function | 4-Way Directional |
| Voltage - Supply5VDCCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Contact Material-Contact Finish-Mounting TypePanel MountTermination StyleWire LeadsOperating Temperature-40°C ~ 85°CPanel Cutout DimensionsCircular - 25.65mm DiaIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofFeatures- | Functions, Extra | - |
| Current Rating - Voltage Rating - AC - Voltage Rating - DC - Contact Material - Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - Curcular - 25.65mm Dia IP68/69K - Dust Tight, Water Resistant, Waterproof - Curcular - 25.65mm Dia Curcular - 25.65mm Dia Curcular - 25.65mm Dia Curcular - 25.65mm Dia | Output | Analog (Hall Effect) |
| Voltage Rating - AC Voltage Rating - DC Contact Material Contact Finish Mounting Type Panel Mount Termination Style Operating Temperature Panel Cutout Dimensions Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features | Voltage - Supply | 5VDC |
| Voltage Rating - DC Contact Material Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - Contact Material - Contact Material - Circular - 25.65mm Dia IP68/69K - Dust Tight, Water Resistant, Waterproof - Features | Current Rating | - |
| Contact Material - Contact Finish - Mounting Type Panel Mount Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | Voltage Rating - AC | - |
| Contact Finish Mounting Type Panel Mount Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | Voltage Rating - DC | - |
| Mounting Type Panel Mount Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | Contact Material | - |
| Termination Style Wire Leads Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | Contact Finish | - |
| Operating Temperature -40°C ~ 85°C Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | Mounting Type | Panel Mount |
| Panel Cutout Dimensions Circular - 25.65mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | Termination Style | Wire Leads |
| Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - | Operating Temperature | -40°C ~ 85°C |
| Features - | Panel Cutout Dimensions | Circular - 25.65mm Dia |
| | Ingress Protection | IP68/69K - Dust Tight, Water Resistant, Waterproof |
| Report errors? | Features | - |
| | | Report errors? |

TSDA2S02A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TSDA2S02A Payment Methods


































If you have any question about TSDA2S02A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com