



TSX9292IYDT Information

Heisener.com

For Reference Only

Part Number TSX9292IYDT

Manufacturer STMicroelectronics

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description LARGE BANDWIDTH (16MHZ), RAIL-TO

Package 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TSX9292IYDT Specifications

Manufacturer Part Number Manufacturer STMicroelectronics Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type CMOS Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 27V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset 4mV Current - Supply 2.8mA Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type CMOS Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 27V/µs Gain Bandwidth Product 16MHz -3db Bandwidth - Current - Input Bias 10pA Voltage - Input Offset 4mV Current - Supply 2.8mA Current - Output / Channel 74mA Voltage - Supply, Single/Dual (±) 4V ~ 16V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Manufacturer Part Number	TSX9292IYDT
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type CMOS Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 27V/µs Gain Bandwidth Product 16MHz -3db Bandwidth - Current - Input Bias 10pA Voltage - Input Offset 4mV Current - Supply 2.8mA Current - Output / Channel 74mA Voltage - Supply, Single/Dual (±) 0perating Temperature 40°C ~ 125°C Mounting Type Surface Mount	Manufacturer	STMicroelectronics
Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type CMOS Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 27V/µs Gain Bandwidth Product 16MHz -3db Bandwidth - Current - Input Bias 10pA Voltage - Input Offset 4mV Current - Supply 2.8mA Current - Output / Channel 74mA Voltage - Supply, Single/Dual (±) 4V ~ 16V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Category	Integrated Circuits (ICs)
Series		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 27V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 10pA Voltage - Input Offset 4mV Current - Supply 2.8mA Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature 40°C ~ 125°C Mounting Type CMOS Rail-to-Rail 2 2 27V/µs 16MHz - - - - - - - - - - - - -	Package	8-SOIC (0.154", 3.90mm Width)
Number of Circuits2Output TypeRail-to-RailSlew Rate $27V/\mu s$ Gain Bandwidth Product $16MHz$ -3db Bandwidth-Current - Input Bias $10pA$ Voltage - Input Offset $4mV$ Current - Supply $2.8mA$ Current - Output / Channel $74mA$ Voltage - Supply, Single/Dual (\pm) $4V \sim 16V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Mounting TypeSurface Mount	Series	-
Output Type Rail-to-Rail Slew Rate $27V/\mu s$ Gain Bandwidth Product $16MHz$ -3db Bandwidth - Current - Input Bias $10pA$ Voltage - Input Offset $4mV$ Current - Supply $2.8mA$ Current - Output / Channel $74mA$ Voltage - Supply, Single/Dual (\pm) $4V \sim 16V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Mounting Type Surface Mount	Amplifier Type	CMOS
Slew Rate $27V/\mu s$ Gain Bandwidth Product $16MHz$ -3db Bandwidth - Current - Input Bias $10pA$ Voltage - Input Offset $4mV$ Current - Supply $2.8mA$ Current - Output / Channel $74mA$ Voltage - Supply, Single/Dual (\pm) $4V \sim 16V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Mounting Type Surface Mount	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth -Current - Input Bias 10pA Voltage - Input Offset 4mV Current - Supply 2.8mA Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature Mounting Type 16MHz - 16MHz - 16MHz - 4mV 5urrent - Output Bias 10pA 4mV 2.8mA 4v ~ 16V 5urface Mount	Output Type	Rail-to-Rail
-3db Bandwidth - Current - Input Bias 10pA Voltage - Input Offset 4mV Current - Supply 2.8mA Current - Output / Channel 74mA Voltage - Supply, Single/Dual (±) 4V ~ 16V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Slew Rate	27V/μs
Current - Input Bias 10pA Voltage - Input Offset 4mV Current - Supply 2.8mA Current - Output / Channel 74mA Voltage - Supply, Single/Dual (±) 4V ~ 16V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Gain Bandwidth Product	16MHz
Voltage - Input Offset $4mV$ Current - Supply $2.8mA$ Current - Output / Channel $74mA$ Voltage - Supply, Single/Dual (\pm) $4V \sim 16V$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting TypeSurface Mount	-3db Bandwidth	-
Current - Supply 2.8mA Current - Output / Channel 74mA Voltage - Supply, Single/Dual (±) 4V ~ 16V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Current - Input Bias	10pA
Current - Output / Channel 74mA Voltage - Supply, Single/Dual (\pm) 4V ~ 16V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Voltage - Input Offset	4mV
Voltage - Supply, Single/Dual (\pm) 4V ~ 16V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Current - Supply	2.8mA
Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Current - Output / Channel	74mA
Mounting Type Surface Mount	Voltage - Supply, Single/Dual (±)	4V ~ 16V
	Operating Temperature	-40°C ~ 125°C
	Mounting Type	Surface Mount
Package / Case 8-SOIC (0.154", 3.90mm Width)	Package / Case	8-SOIC (0.154", 3.90mm Width)
Supplier Device Package 8-SO	Supplier Device Package	8-SO
Report erro		Report errors?

TSX9292IYDT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TSX9292IYDT Payment Methods



















TSX9292IYDT Shipping Methods













If you have any question about TSX9292IYDT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com