



TTH5018RJ Information

Heisener.com

Part Number TTH5018RJ

Manufacturer TE Connectivity AMP Connectors

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 18 OHM 5% 50W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TTH5018RJ Specifications

Manufacturer Part NumberTTH5018RJManufacturerTE Connectivity AMP ConnectorsCategoryResistorsChassis Mount ResistorsPackageRadial, TubularSeriesTTHResistance18 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 200°CFeaturesFlame Proof, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension-Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial Tubular	<u>-</u>	
CategoryResistorsPackageRadial, TubularSeriesTTHResistance18 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 200°CFeaturesFlame Proof, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension-Height - Seated (Max)-Lead StyleSolder Lugs	Manufacturer Part Number	TTH5018RJ
PackageRadial, TubularSeriesTTHResistance18 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 200°CFeaturesFlame Proof, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension-Height - Seated (Max)-Lead StyleSolder Lugs	Manufacturer	TE Connectivity AMP Connectors
PackageRadial, TubularSeriesTTHResistance18 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 200°CFeaturesFlame Proof, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension-Height - Seated (Max)-Lead StyleSolder Lugs	Category	Resistors
SeriesTTHResistance18 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 200°CFeaturesFlame Proof, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension-Height - Seated (Max)-Lead StyleSolder Lugs		Chassis Mount Resistors
Resistance 18 Ohms Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 200°C Features Flame Proof, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension - Height - Seated (Max) Lead Style Solder Lugs	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 200°C Features Flame Proof, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension - Height - Seated (Max) Lead Style Solder Lugs	Series	TTH
Power (Watts) Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 200°C Features Flame Proof, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension - Height - Seated (Max) Lead Style Solder Lugs	Resistance	18 Ohms
Composition Wirewound ±400ppm/°C Operating Temperature -55°C ~ 200°C Features Flame Proof, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension - Height - Seated (Max) Lead Style Wirewound ### Wirewound #### Authorized **Solder Lugs **Coating Housing Type Vitreous Enamel Coated **Solder Lugs **Solder Lugs **Tourized **Tourized **Dimension **Tourized **Tourized **Solder Lugs **Tourized **Tourized	Tolerance	±5%
Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 200°C Features Flame Proof, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension - Height - Seated (Max) Lead Style Solder Lugs	Power (Watts)	50W
Operating Temperature -55°C ~ 200°C Features Flame Proof, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension - Height - Seated (Max) Lead Style Solder Lugs	Composition	Wirewound
Features Flame Proof, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension	Temperature Coefficient	±400ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included)	Operating Temperature	-55°C ~ 200°C
Mounting Feature Brackets (not included) Size / Dimension - Height - Seated (Max) - Lead Style Solder Lugs	Features	Flame Proof, Safety
Size / Dimension - Height - Seated (Max) - Lead Style Solder Lugs	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) Lead Style Solder Lugs	Mounting Feature	Brackets (not included)
Lead Style Solder Lugs	Size / Dimension	-
	Height - Seated (Max)	-
Package / Case Radial Tubular	Lead Style	Solder Lugs
radial, Tubulal	Package / Case	Radial, Tubular
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

TTH5018RJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TTH5018RJ Payment Methods



















TTH5018RJ Shipping Methods













If you have any question about TTH5018RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com