



TUNS300F28 Information

www.hersaum.com

Part Number TUNS 300 F28
Manufacturer Cosel USA, Inc.

Category Power Supplies - Board Mount

AC DC Converters

Description AC/DC CONVERTER

Package 7-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TIINS300F28	Specifications
1 UNOSUUT 40	Specifications

Manufacturer Part Number TUNS300F28 Manufacturer Cosel USA, Inc. Category Power Supplies - Board Mount AC DC Converters Package 7-DIP Module Series TUN Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11A Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm) Report errors?	•		
Category Power Supplies - Board Mount AC DC Converters Package 7-DIP Module Series TUN Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output (Max) 11A Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Manufacturer Part Number	TUNS300F28	
Package 7-DIP Module Series TUN Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11A Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Manufacturer	Cosel USA, Inc.	
Package 7-DIP Module Series TUN Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11A Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Category	Power Supplies - Board Mount	
Series TUN Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11A Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)		AC DC Converters	
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11A Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Package	7-DIP Module	
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11A Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Series	TUN	
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11A Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Type	Enclosed	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 11A Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Features Universal Input Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension - Voltage - Output 2 - Universal Input - Universal	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 4 - Current - Output (Max) 11A Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case Size / Dimension	-	28V	
Voltage - Output 4 Current - Output (Max) 11A Power (Watts) Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension -40°C ~ 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) 300W Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 11A 300W Applications ITE (Commercial) Universal Input -40°C ~ 100°C (With Derating) Features -40°C ~ 100°C (With Derating) Through Hole 14.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Current - Output (Max)	11A	
Features Universal Input Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Power (Watts)	300W	
Operating Temperature -40°C ~ 100°C (With Derating) Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Applications	ITE (Commercial)	
Efficiency 89% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Features	Universal Input	
Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Operating Temperature	-40° C ~ 100° C (With Derating)	
Package / Case 7-DIP Module Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Efficiency	89%	
Size / Dimension 4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	Mounting Type	Through Hole	
	Package / Case	7-DIP Module	
Report errors?	Size / Dimension	4.62" L x 2.42" W x 0.50" H (117.3mm x 61.5mm x 12.7mm)	
		Report errors	?

TUNS300F28 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TUNS300F28 Payment Methods



















TUNS300F28 Shipping Methods













If you have any question about TUNS300F28, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com