

TWM3J56R

TWM3J56R Information



For Reference Only

Part Number	TWM3J56R	
Manufacturer	Ohmite	
Category	Resistors Through Hole Resistors	
Description	RES 56 OHM 3W 5% RADIAL	
Package	Radial	
	For the pricing/inventory/lead time, please contact	
us		
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



TWM3J56R Specifications

Manufacturer Part NumberTWM3J56RManufacturerOhmiteCategoryResistorsPackageRadialPackageRadialSeriesTWMResistance56 OhmsTolerance±5%Power (Watts)3WCompositionMetal Oxide FilmFeaturesFlame Proof, SafetyTemperature Coefficient±350pm/°COperating Temperature55°C ~ 275°CPackage / CaseRadial LeadSupplier Device PackageRadial LeadSize / Dimension0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2Failure Rate-		
CategoryResistorsThrough Hole ResistorsPackagePackageRadialSeriesTWMResistance56 OhmsTolerance±5%Power (Watts)SWCompositionFeaturesFlame Proof, SafetyTemperature Coefficient±350pm/°COperating Temperature55°C ~ 275°CPackage / CaseSupplier Device PackageSize / DimensionHeight - Seated (Max)Number of Terminations2	Manufacturer Part Number	TWM3J56R
Through Hole ResistorsPackageRadialSeriesTWMResistance56 OhmsTolerance±5%Power (Watts)3WCompositionMetal Oxide FilmFeaturesFlame Proof, SafetyTemperature Coefficient±350ppm/°COperating Temperature-55°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)2	Manufacturer	Ohmite
PackageRadialSeriesTWMResistance56 OhmsTolerance±5%Power (Wats)3WCompositionMetal Oxide FilmFeaturesFlame Proof, SafetyTemperature Coefficient±350pm/°COperating Temperature-55°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Category	Resistors
SeriesTWMResistance56 OhmsTolerance±5%Power (Watts)3WCompositionMetal Oxide FilmFeaturesFlame Proof, SafetyTemperature Coefficient±350pm/°COperating Temperature-55°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2		Through Hole Resistors
Resistance56 OhmsTolerance±5%Power (Watts)3WCompositionMetal Oxide FilmFeaturesFlame Proof, SafetyTemperature Coefficient±350pm/°COperating Temperature-55°C ~ 275°CPackage / CaseRadialSupplier Device Package0.492° L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Package	Radial
Tolerance±5%Power (Watts)3WCompositionMetal Oxide FilmFeaturesFlame Proof, SafetyTemperature Coefficient±350pm/°COperating Temperature-55°C ~ 275°CPackage / CaseRadial LeadSupplier Device Package0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Series	TWM
Power (Watts)3WCompositionMetal Oxide FilmFeaturesFlame Proof, SafetyTemperature Coefficient±350ppm/°COperating Temperature-55°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Resistance	56 Ohms
CompositionMetal Oxide FilmFeaturesFlame Proof, SafetyTemperature Coefficient±350pm/°COperating Temperature-55°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Tolerance	$\pm 5\%$
FeaturesFlame Proof, SafetyTemperature Coefficient±350ppm/°COperating Temperature-55°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Power (Watts)	3W
Temperature Coefficient±350ppm/°COperating Temperature-55°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Composition	Metal Oxide Film
Operating Temperature-55°C ~ 275°CPackage / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Features	Flame Proof, Safety
Package / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Temperature Coefficient	±350ppm/°C
Supplier Device PackageRadial LeadSize / Dimension0.492" L x 0.354" W (12.50mm x 9.00mm)Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Operating Temperature	-55°C ~ 275°C
Number of Terminations 0.492" L x 0.354" W (12.50mm x 9.00mm) 1.024" (26.00mm) 1.024" (26.00mm)	Package / Case	Radial
Height - Seated (Max)1.024" (26.00mm)Number of Terminations2	Supplier Device Package	Radial Lead
Number of Terminations 2	Size / Dimension	0.492" L x 0.354" W (12.50mm x 9.00mm)
	Height - Seated (Max)	1.024" (26.00mm)
Failure Rate -	Number of Terminations	2
	Failure Rate	-
Report error		Report errors?

TWM3J56R Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

TWM3J56R Payment Methods Image: Ima

If you have any question about TWM3J56R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com