

## TX12-60V

#### **TX12-60V Information**

Heisener.com Gittal service statisties	Part Number Manufacturer Category Description Package	TX12-60V Bourns Inc. Transformers Power Transformers XFRMR SEMI-TORO 12VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **TX12-60V Specifications**

Manufacturer Part NumberTX12-60VManufacturerBourns Inc.CategoryTransformersPackage-SeriesTXTypeSemi-ToroidalVoltage - PrimaryI15V, 230VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 200mA, Series 100mAPrimary Winding(s)DualSecondary Winding(s)DualPower - Max12 VAMounting TypeThrough HoleTermination StyleS0.80mm L x 50.80mm WHeight - Seated (Max)2000VrmsWeight-		
CategoryTransformersPackage-Package-SeriesTXTypeSemi-ToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 200mA, Series 100mAPrimary Winding(s)DualSecondary Winding(s)DualPower - Max12 VANouring TypeThrough HolePormination StyleSomm L x 50.80mm WSize / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)200Vrms	Manufacturer Part Number	TX12-60V
PackagePower TransformersPackage-SeriesTXTypeSemi-ToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 200mA, Series 100mAPrimary Winding(s)DualSecondary Winding(s)DualPower - Max12 VAPower - MaxPrinary MindingSize / Dimension50.80mm L x 50.80mm WSize / Dimension50.80mm L x 50.80mm WVoltage - Isolation2000Vrms	Manufacturer	Bourns Inc.
Package.SeriesTXTypeSemi-ToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 200mA, Series 100mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleSize / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)200Vrms	Category	Transformers
SeriesTXTypeSemi-ToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 200mA, Series 100mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StyleSecondary Winding(s)Size / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)200Vrms		Power Transformers
TypeSemi-ToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 200mA, Series 100mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StyleSecondary LSize / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)200Vrms	Package	-
SyrtSince AnnualVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 200mA, Series 100mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StyleS0.80mm L x 50.80mm WSize / Dimension27.18mmHeight - Seated (Max)2000Vrms	Series	ТХ
Voltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 200mA, Series 100mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StyleSo80mm L x 50.80mm WSize / Dimension27.18mmHeight - Seated (Max)2000Vrms	Туре	Semi-Toroidal
Current - Output (Max)Parallel 200mA, Series 100mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)27.18mmVoltage - Isolation2000Vrms	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)27.18mmVoltage - Isolation2000Vrms	Voltage - Secondary (Full Load)	Parallel 60V, Series 120V
Secondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)27.18mmVoltage - Isolation2000Vrms	Current - Output (Max)	Parallel 200mA, Series 100mA
Center TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)27.18mmVoltage - Isolation2000Vrms	Primary Winding(s)	Dual
Power - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)27.18mmVoltage - Isolation2000Vrms	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)27.18mmVoltage - Isolation2000Vrms	Center Tap	No
Termination StylePC PinSize / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)27.18mmVoltage - Isolation2000Vrms	Power - Max	12 VA
Size / Dimension50.80mm L x 50.80mm WHeight - Seated (Max)27.18mmVoltage - Isolation2000Vrms	Mounting Type	Through Hole
Height - Seated (Max)27.18mmVoltage - Isolation2000Vrms	Termination Style	PC Pin
Voltage - Isolation 2000Vrms	Size / Dimension	50.80mm L x 50.80mm W
	Height - Seated (Max)	27.18mm
Weight -	Voltage - Isolation	2000Vrms
	Weight	-
Report errors?		Report errors?

#### **TX12-60V Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about TX12-60V, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com