

TX2-L-9V-1 Information

Heisener.com

Part Number TX2-L-9V-1

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 9V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TX2-L-9V-1 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package - Series TX Relay Type Telecom Coil Type Latching, Single Coil Coil Current 11.1mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 1220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole PC Pin Report errors?		
CategoryRelaysPackage-SeriesTXRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current11.1mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	TX2-L-9V-1
Package-SeriesTXRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current11.1mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - Series TX Relay Type Telecom Coil Type Latching, Single Coil Coil Current 11.1mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Category	Relays
Series TX Relay Type Telecom Coil Type Latching, Single Coil Coil Current 11.1mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Single CoilCoil Current11.1mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeLatching, Single CoilCoil Current11.1mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	TX
Coil Current Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Relay Type	Telecom
Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Release Time Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Current	11.1mA
Contact Rating (Current) Switching Voltage 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	9VDC
Switching Voltage 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style 6.75 VDC	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	220VDC - Max
Operate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	6.75 VDC
Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	4ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	Sealed - Fully
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

TX2-L-9V-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TX2-L-9V-1 Payment Methods



















TX2-L-9V-1 Shipping Methods













If you have any question about TX2-L-9V-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com