

TX2-L-H-12V

TX2-L-H-12V Information

www.helsener.com	 TX2-L-H-12V Panasonic Electric Works Relays Signal Relays, Up to 2 Amps RELAY TELECOM DPDT 2A 12V - For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



TX2-L-H-12V Specifications

Manufacturer Part NumberTX2-L-H-12VManufacturer QPanasonic Electric WorksCategoryRelaysBackageSignal Relays, Up to 2 AmpsPackage-SeriesTXRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage (Max)9 VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Coperate TimeAmsRelease TimeSeided - FullyManufacturesSeided - FullyManufacturesCoil FullyFeaturesCoin HoleTurn On Voltage (Max)PC FunCortex TimeAmsRelease TimeSeided - FullyFeaturesCale TurlyFeaturesPance TurlyFeaturesPance TurlySeided - FullyTurout Seide Seide - FullyFeaturesPance TurlyFeaturesPance TurlyFeaturesSeide - FullyFeaturesFullyFeaturesPance FullyFeaturesPance Fully <th></th> <th></th>		
Category Relays Signal Relays, Up to 2 Amps Package - Package - Series TX Relay Type Telecom Coll Type Iatching, Single Coll Coll Current 8.3mA Coll Otage I2VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 9.VDC - Max Turn Of Voltage (Max) 9.VDC Turn Off Voltage (Max) 9.VDC Querter Time - Operate Time Mas Release Time Mas Features Seade - Fully Mounting Type Through Hole	Manufacturer Part Number	TX2-L-H-12V
Signal Relays, Up to 2 AmpsPackage-SeriesTXRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage (Max)9 VDCTurn On Voltage (Max)9 VDCCurrent Fine4msRelease Time4msRelease TimeSealed - FullyMounting TypeThrough Hole	Manufacturer	Panasonic Electric Works
Package-SeriesTXRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage9 VDC - MaxTurn On Voltage (Max)-Operate Time4msRelease TimeSealed - FullyMounting TypeTrough Hole	Category	Relays
SeriesTXRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Coperate Time4msRelease TimeSealed - FullyMounting TypeThrough Hole		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)24Switching Voltage20VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time4msRelease TimeSaled - FullyFeaturesSaled - FullyMounting TypeThrough Hole	Package	-
Coil TypeLatching, Single CoilCoil TypeKatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time4msRelease TimeSaled - FullyFeaturesSaled - FullyMounting TypeThrough Hole	Series	TX
Coil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time4msRelease TimeSaled - FullyFeaturesSaled - FullyMounting TypeThrough Hole	Relay Type	Telecom
Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage20VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time4msRelease TimeSealed - FullyFeaturesSealed - FullyMounting TypeThrough Hole	Coil Type	Latching, Single Coil
Contact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time4msRelease TimesSealed - FullyFoaturegSealed - FullyMounting TypeThrough Hole	Coil Current	8.3mA
Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time4msRelease TimesSealed - FullyMounting TypeThrough Hole	Coil Voltage	12VDC
Switching Voltage220VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough Hole	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough Hole	Contact Rating (Current)	2A
Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough Hole	Switching Voltage	220VDC - Max
Operate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough Hole	Turn On Voltage (Max)	9 VDC
Release Time4msFeaturesSealed - FullyMounting TypeThrough Hole	Turn Off Voltage (Min)	-
Features Sealed - Fully Mounting Type Through Hole	Operate Time	4ms
Mounting Type Through Hole	Release Time	4ms
	Features	Sealed - Fully
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

TX2-L-H-12V Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

TX2-L-H-12V Payment Methods



TX2-L-H-12V Shipping Methods



If you have any question about TX2-L-H-12V, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com