

## **TX2SL-48V Information**



For Reference Only

Part Number TX2SL-48V

Manufacturer Panasonic Electric Works

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY TELECOM DPDT 2A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **TX2SL-48V Specifications**

Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Signal Relays, Up to 2 Amps  Package  - Series  TX  Relay Type  Telecom  Coil Type  Non Latching  Coil Current  5.6mA  Coil Voltage  48VDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  2A  Switching Voltage  220VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VDC  Operate Time  4ms  Release Time  4ms  Features  Sealed - Fully  Mounting Type  Surface Mount  Termination Style		
CategoryRelaysPackage-SeriesTXRelay TypeTelecomCoil TypeNon LatchingCoil Current5.6mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	TX2SL-48V
Package Series TX Relay Type Telecom Coil Type Non Latching Coil Current Soma Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time Ams Release Time Features Sealed - Fully Mounting Type Surface Mount Termination Style Series TX TX Ams Turn O 2 A Switching Voltage And Coil Volt	Manufacturer	Panasonic Electric Works
Package - Series TX Relay Type Telecom Coil Type Non Latching Coil Current 5.6mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Surface Mount Termination Style Gold Max Called And Surface Mount Telecom TX TX TX Turn Off Ann And And And And And And And And And	Category	Relays
SeriesTXRelay TypeTelecomCoil TypeNon LatchingCoil Current5.6mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current5.6mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Current5.6mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Series	TX
Coil Current 5.6mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	Telecom
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  220VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VDC  Operate Time  4ms  Release Time  4ms  Release Time  5eatures  Sealed - Fully  Mounting Type  Surface Mount  Termination Style  Gull Wing	Coil Current	5.6mA
Contact Rating (Current)  Switching Voltage  220VDC - Max  Turn On Voltage (Max)  36 VDC  Turn Off Voltage (Min)  4.8 VDC  Operate Time  4ms  Release Time  4ms  Features  Sealed - Fully  Mounting Type  Surface Mount  Termination Style  Gull Wing	Coil Voltage	48VDC
Switching Voltage 220VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Surface Mount Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VDC  Operate Time  4ms  Release Time  4ms  Features  Sealed - Fully  Mounting Type  Surface Mount  Termination Style  Gull Wing	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  Sealed - Fully  Mounting Type  Surface Mount  Termination Style  Gull Wing	Switching Voltage	220VDC - Max
Operate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Turn On Voltage (Max)	36 VDC
Release Time 4ms Features Sealed - Fully Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	4.8 VDC
Features Sealed - Fully Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	4ms
Mounting TypeSurface MountTermination StyleGull Wing	Release Time	4ms
Termination Style Gull Wing	Features	Sealed - Fully
	Mounting Type	Surface Mount
	Termination Style	Gull Wing
Report errors?		Report errors?

### **TX2SL-48V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **TX2SL-48V Payment Methods**





















## **TX2SL-48V Shipping Methods**













If you have any question about TX2SL-48V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com